




PRESSING KITS AND FRUIT SIZES CITROCASA 8000 ADVANCE SERIES



<p>Pressing Kit <i>Be sure to follow the size specifications given for each pressing kit. Using the wrong size fruit can degrade the quality of the juice and damage the equipment!</i></p>	<p>Large Pressing Kit (Grapefruit Kit)</p> 	<p>Standard Pressing Kit (Orange Kit)</p> 	<p>Small Pressing Kit (Lemon/Lime Kit)</p> 
<p>Fruit size: diameter</p>	<p>3.15 - 3.50 in (80 - 89 mm)</p>	<p>2.55 - 3.14 in (65 - 80 mm)</p>	<p>1.96 - 2.55 in (50 - 65 mm)</p>
<p>Fruit per minute</p>	<p>Approx. 40 pieces of fruit</p>	<p>Approx. 40 pieces of fruit</p>	<p>Approx. 40 pieces of fruit</p>
<p>Additional Information <i>Attention: ALL pressing kit parts used must have the same color! Do not mix parts of different color!</i></p>	<p>Color: GREEN Suitable for large oranges, smaller grapefruit SOLD SEPARATELY</p>	<p>Color: ORANGE Suitable for regular-sized oranges</p>	<p>Color: YELLOW Suitable for lemons, limes, small oranges SOLD SEPARATELY</p>



- ✓ **Follow the size specifications!**
- ✓ **Do not use frozen fruit or fruit that is too cold!**
- ✓ **Always use clean, quality juice fruit! Only use citrus fruit!**

SOME TIPS FOR JUICING SMALL AND LARGE FRUIT:

- Be sure to use the **proper fruit supply tunnel** provided with the kit!
- DO NOT mix parts from different pressing kits. **ALL pressing kit parts must have the SAME COLOR!**
- Be sure to control the flow of fruit into the juicing area to avoid fruit jams: **Oblong fruit** with pointy ends (e.g. lemons), **flat fruit** (e.g. tangerines), or **large fruit** may need staff attention to manage flow.

**DO NOT SPRAY
OR HOSE DOWN
THE MACHINE!**

OPERATION AND CLEANING DOS AND DON'TS



At Citrus America, we want to make sure that you can enjoy your juicing equipment for many years to come. To do so, please note the following:

- ✓ FOLLOW THE **FRUIT SPECIFICATIONS** provided (see other side).
- ✓ DO **NOT OVERLOAD** the fruit basket: **max. weight: 46 lb!**
- ✓ REGULARLY **EMPTY THE PEEL BUCKETS** to avoid back-up blockages and serious machine damage.
- ✓ USE THE **ON/OFF BUTTON** on the display or on the side of the machine to STOP THE JUICING OPERATION.
 - **Do not shut off the main power switch or unplug while the machine is running.** This will cause the pressing elements to stop in the wrong position and may require special steps to reset the machine.
- ✓ **CLEAN THE MACHINE AT LEAST ONCE A DAY** to keep it hygienic and safe.
- ✓ **UNPLUG** THE MACHINE before cleaning it.
 - **Do not jerk the power cord.** Remove the plug by grasping it.
- ✓ FOLLOW THE **CLEANING INSTRUCTIONS** provided.
- ✓ USE ONLY **FRESH, CLEAN, WARM WATER** AND A **SOFT TOWEL** to clean the **HOUSING** and the **O-RING SEALS**.
 - **Do not use chemical cleaning agents. Do not use abrasive scouring pads or cleaners.** Chemicals and abrasives will damage the O-ring seals and lead to costly repairs.
- ✓ **THE PLASTIC FRONT COVER, THE SIDE CHUTES, AND THE JUICE TANK (8000 XB) ARE HANDWASH ONLY!**
 - **Do not place the front cover, the side chutes, and the juice tank in the dishwasher.**
- ✓ **CLEAN ALL OTHER REMOVABLE PARTS IN THE DISHWASHER** or clean them thoroughly by hand.
- ✓ **DO NOT PLACE THE MACHINE UNDER RUNNING WATER.**
- ✓ **ASSEMBLE THE MACHINE IN THE REVERSE ORDER** of disassembly.
 - **Hand tighten all screws. Install the blade with the sharp edge up. CAUTION: KNIFE IS SHARP!**
- ✓ ALWAYS **STABILIZE** THE MACHINE when moving it around on the rolling cabinet.
 - **Move it slowly and carefully** over thresholds, drains, uneven floor areas and through narrow spaces.
 - **CAUTION:** If not stabilized and moved too fast, **THE MACHINE CAN TIP OVER AND BREAK!**

TECH SUPPORT: 1-855-MY-CITRO (1-855-692-4876)
technical@citrusamerica.com

