

Stainless design. Stellar performance. Superior value.

Project name:	
Location:	
Item #:	_ QTY:
Model #:	

AR49 | TWO DOOR REACH-IN RI REACH-IN REFRIGERATOR



AR49

- Tested to NSF Standard 7 requirements for open food storage.
- Standard with full two year parts and labor warranties and a five year compressor warranty.
- Arctic Air products must pass numerous quality control inspections throughout the manufacturing process.
- All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas.

Energy Star approved



COMMERCIAL FREEZERS & REFRIGERATORS





Exterior cabinet construction consists of full stainless steel front and sides.

Interior cabinet is bright white aluminum liner with full stainless steel floor with coved corners.

Six adjustable, heavy-duty epoxy coated wire shelves.

Self-contained capillary tube system using environmentally friendly R290 Hydrocarbon gas.

Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.

Bottom mounted compressor for more efficient operation in coolest area of kitchen.

Front accessible, bottom mounted condensing unit is mounted on slide out rack for easy maintenance.



Electronic thermostat with external digital LED display for accurate control and easy reading.

Vaulted self closing doors that remain open at 90 degrees.

Magnetic door gasket is removable and replaceable without tools.

Lockable door with foamed-in-place recessed handle.

Larger fan motors and blades for more efficient air flow ensuring faster recovery times.

Easy to mount plate casters (two lockable) are standard with all units.

Unit can hold an additional (2) optional stainless steel full size sheet pan racks – part # 64900K behind each door, some field install is required.

Tested to NSF Standard 7 requirements for open food storage.

Standard with full two year parts and labor warranties and a five year compressor warranty.

STAINLESS STEEL DESIGN . STELLAR PERFORMANCE . SUPERIOR VALUE

Model Number	Exter Width	rnal Dimer Depth	nsions Height*	Doors	Epoxy Coated Shelves (horizontal)	Cubic Feet	Temperature Range	Cord Length	НР	AMPS	REF	NEMA Plug	Crate Weight
AR49	54"	32.75"	82.75"	2	6	49	33°F to 41°F	8′	1/3	4.5	R290	5-15P	455Llbs









