



Code	Description	Length (mm/inch)	Depth (mm/inch)	Height (mm/inch)	Weight (kg/ lb)	Capacity Pieces
CR-3E	Electrical Chicken Rotisserie	1192.8 / 46.96"	516.5 / 20.34"	818 / 32.2"	108 / 238.09	18
CR-5E	Electrical Chicken Rotisserie	1192.8 / 46.96"	516.5 / 20.34"	1180 / 46.46"	140 / 308.64	30
CR-8E	Electrical Chicken Rotisserie	1196.8 / 47.11"	571.5 / 22.5"	1856.2 / 73.07"	214/ 471.78	48

TECHNICAL SPECIFICATIONS

- Each resistance can be controlled separately.
- Heat resistant tempered glass doors.
- Spear and door handles are made of heat resistant bakelite.
- Electrical fitting is durable to high temperatures.
- Steel gear system provides quiet operation.
- Stainless steel body.
- Provides simple maintain and easy cleaning.
- Each spear takes 6 chicken.

CR-3E

Power : 9,9 KW
Voltage : 208V-3P/60HZ

CR-5E

Power : 16,5 KW
Voltage : 208V-3P/60HZ

CR-8E

Power : 26,4 KW
Voltage : 208V-3P/60HZ