

Refrigeration Equipment 2-Solid Door Back Bar Refrigerator Black 49" Long

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



738269 (KCHBB48S)

2-Solid Door Back Bar
Refrigerator Black 49" Long

Short Form Specification

Item No. _____

2-door Back bar refrigerator. Exterior back and bottom panels in galvanized steel, top panel in 304 stainless steel and exterior side panels in painted steel; interior back, side, and top panels in 430 stainless steel, interior bottom panel and worktop in 304 stainless steel. Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and temperature control. Heavy duty adjustable shelves and stay-open self-closing doors.

R290 gas in refrigeration circuit.

ETL Safety and Sanitation certified.

3/5 Years warranty.

Main Features

- External digital temperature display.
- External temperature display.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Locking doors.
- Heavy duty Vinyl coated steel shelves.
- Cabinet completely insulated with high density polyurethane for low environmental impact.


Construction

- Lockable door.
- Self-closing door with 90-degree stay-open feature.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.

Sustainability

- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.

APPROVAL: _____



Electric

Supply voltage:	
738269 (KCHBB48S)	115 V/1 ph/60 Hz
Electrical power, max:	0.31 kW
Plug type:	USA NEMA 5-15P

Capacity:

Gross capacity:	12.5 cu.feet
------------------------	--------------

Key Information:

Door hinges:

External dimensions, Width: 49 1/16" (1247 mm)

External dimensions, Depth: 24 7/16" (620 mm)

External dimensions, Height: 36 1/4" (920 mm)

Number and type of doors: 2 Full

Internal Dimensions (depth): 20 " / (508 mm)

Internal Dimensions (height): 28 " / (711.2 mm)

Internal Dimensions (width): 36 " / (914.4 mm)

Shipping height: 41 5/16" (1050 mm)

Shipping weight: 256 lbs (116 kg)

Shipping volume: 32.45 ft³ (0.92 m³)

Number and type of grids (included): 4 - Vinyl-Coated Steel

Type of external material: Black Prepainted Steel

Type of internal material: Stainless Steel

Warranty: 3 / 5 years

Approvals ETL C&US;ETL SANITATION

Refrigeration Data

Current absorbed: 3 Amps

Compressor power: 1/5 hp

Operating temperature min.: 32 °F

Operating temperature max.: 41 °F

Condenser type: Fin & tube

Defrost type: Auto Defrost

Sustainability

Current consumption: 3 Amps

Refrigerant type: R290

GWP Index: 3

Refrigerant weight: 110 g



Refrigeration Equipment
2-Solid Door Back Bar Refrigerator Black 49" Long

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.