





Fryer Baskets Sold Separately

Item No.

R160

Frozen Food Dispenser

Features

Dispenses and stores frozen fries directly into fryer basket. Ensuring that the fries are cooked from frozen, results in improved product quality, consistency, and yield. Unit is designed for simple daily cleaning of cabinet and refrigeration filter. Provides storage of up to two baskets, flexible store configuration for left- or right-hand door opening. Self contained environmentally friendly refrigeration system using R290 with cold wall construction.

Dispensing

Push button dispensing system enables the operator to fill one basket and slide another basket back into the fill position.


Operation


Operation of the R160 Frozen Food Dispenser is easily controlled by a power switch, simple visual portion control, and an ergonomic basket fill location.











Weights	lb.		kg		
Net	257		117		
Crated	289		131		
*For reference only					
	lb.		kg		
Hopper Capacity	36		16.3		
Dimensions	in.		cm		
Width	16.5		42		
Depth	28	71			
Height	67.75	67.75 173			
Electrical	Total	Plug Type	Poles (P)		
	Amps		Wires (W)		
115/60/1 Air	8.0	NEMA 5-15P	2P+G		
220-240/50/60/1 Air	4.6	IEC 60309 6H	2P+G		
Power Cord Length	8 ft. (2	2.43 m)			

This unit may be manufactured with other electrical characteristics and may have additional regulatory agency approvals. Consult the local Taylor distributor for other electrical characteristics and agency approvals based on specific electrical and country requirements.

(For exact electrical information, approval marks, and refrigerant, always refer to the data label of the unit.)

Continuing research results in steady improvements. Therefore, these specifications are subject to change without notice.

Bidding Specs										
Electrical:	Volt	Hz_		ph						
	Neutral:	□Yes	□No	Cooling:	□Air	□Water	□NA			
Options:										

All options may not be available in combination with others or with all electrical or cooling configurations. Please consult your local Taylor distributor.

Authorized Taylor Distributor

Specifications

Electrical

One dedicated electrical connection is required. See the electrical chart for the proper electrical requirements. Manufactured to be cord connected. Consult your local Taylor distributor for cord and receptacle specifications as local codes allow.

Refrigeration System

One approximately 1,250 BTU/hr. R-290 system. (BTUs may vary depending on compressor used)

Note: Consult local Taylor distributor for refrigerant configurations.

Air-Cooled

Minimum 4 in. (101.6 mm) rear, and 2 in. (508 mm) side clearance. Minimum air clearances must be met to ensure adequate airflow for optimum performance.

Accessories

- · Side-Mount 4 Fryer Basket Rack
- Fryer Basket