

Project:	
Location:	
Item #:	Quantity:
Model #:	

MODEL: ICT-VIP1490B1/3SOLIDLID

COUNTER TOP:

Refrigerated ingredient displays - Glass top

Important: Do only introduce refrigerated products! For daily cleaning, remove products and disconnect unit.



General Strengths

- Sanitation. The interior cabinet is built with rounded corners (extensive radius for easy cleaning). Quick ability to take off shelves and slides for interior cleaning. Each cabinet has a drain at the bottom of the unit. When cleaning the unit make sure the drain hose is routed to a floor drain.
- Lighting. Interior cabinet includes LED lighting, for brighter lighting and energy efficiency, LED saves 90% more energy compared to traditional fluorescent bulbs. Considerably increases product visibility.
- Control systems. Higher precision in managing temperature settings. The ability to adjust temperature ranges to meet end user's requirements.
- 100% Tested. All condenser units tested 100%, in helium chambers to refrigerant leak detections.
- Certified. Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7. EQA audited and certified by internationally recognized firm. ISO 9001:2015 (Quality); ISO 14001:2015 (Environmental); ISO 45001:2018 (Prevention and Worker Safety)

		Dimensions inches) (mm		Doors	Ref.	Ref. Ref.Weight (Lbs.) (gr.)	Temperature Range (ºF)	Cond. Unit (H.P)	(Cu.Ft.)	Case Amps	Net weight
MODELS	W	D	Н				(ºC)		(L)	115V	(Lbs.) (Kg.)
ICT-VIP1490B1/3SOLIDLID	58-3/8	16-1/4	10-1/4	_	R600		39ºF/41ºF	1/6	1.55	1.82	132
	1493	413	260			40	4ºC/6ºC		44		60

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE

















Project:	
Location:	
Item #:	Quantity:
Model #:	

MODEL: ICT-VIP1490B1/3SOLIDLID

COUNTER TOP: Refrigerated ingredient displays – Glass top

STANDARD FEATURES

Exterior

- AISI 304 Stainless Steel,
- Safety glass on the top, closed in the front (facing the customer) and open in the back (facing the operator),
- Sliding doors on the back,
- Levelling feet.

Interior

- AISI 304 Stainless Steel,
- Sealed interior floors and rounded cabinet corners,
- Stainless steel 6" deep pans, included.

OPTIONAL FEATURES

✓ Electrical connections is: 220 - 230 V / 1 ph / 50Hz (plug type varies).

Insulation

- Polyurethane with high density 40kg/m³, CFS free, zero ODP and low GWP.
- Low GWP & Zero ODP effect.

Refrigeration

- Digital temperature controller,
- Cold wall refrigeration system,
- Refrigeration capacity: 973 Btu/h (14ºF) / 190 W (-10ºC).

Electrical



- Cord and NEMA 5-15P plug,
- Electrical connection is 115V/ 1ph / 60 Hz.
- ETL Listen to UL471 Standard and Sanitation classified to NSF7.



















Project:	
Location:	
Item #:	Quantity:
Model #:	


MODEL: ICT-VIP1490B1/3SOLIDLID


COUNTER TOP:

Refrigerated ingredient displays – Glass top

PLAN VIEW

ELEVATION RIGHT VIEW





PLAN VIEW

