




# POWER PACK - AIR COOLED

PREMIUM - 2 PUMP - 7,250 BTUs

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Exterior sight glass to verify glycol bath level.
- Anti-vibration pads reduce motor noise.
- Rugged stainless steel cabinet.



**MMPP4305-PKG**



6-20P\*




\*Units manufactured prior to 2/1/2022 were produced with a 6-15P plug.



[www.micromatic.com](http://www.micromatic.com) • 1 (866) 327-4159

1 HP COMPRESSOR

Job Number: \_\_\_\_\_ Location: \_\_\_\_\_

Part No.	Description	Shipping Weight
 MMPP4305-PKG	Air cooled power pack, 2 pump and motor	98 kg 215 lbs

## Operating Performance

<b>Compressor</b>	1 HP	<b>Refrigerant</b>	R-134a
<b>BTU per hour</b>	7,250	<b>Charge</b>	0.56 kg (20 oz)
<b>Plug Type (NEMA #)</b>	6-20P*	<b>Refrigerant Running Pressure</b>	18 (low) 140 (high)
<b>Cord Length</b>	8'	<b>Bath Capacity</b>	43.5 litre (11.5 gallons)
<b>Voltage</b>	208/230	<b>Pump Type</b>	Rotary Vane
<b>Running</b>	11A	<b>Push In Connector</b>	12.7mm (1/2") O.D.

\*Units manufactured prior to 2/1/2022 were produced with a 6-15P plug.

## Dimensions

