



FEATURES:

 $30"\ x\ 15"\ x\ 12"$ insulated ice bin; 98 lbs. ice capacity.

10"W x 14"L x 7"D dump sink.

Recessed drainboard for glassware storage.

Dual blender/mixer recessed station with 15A - 150V GFI duplex outlet hidden beneath shelf.

Includes two removable plastic bottle racks.

Galvanized legs with adjustable plastic bullet feet.

Adjustable galvanized side cross-bracing.

4" backsplash.

Optional 7-circuit cold plate sealed into the bottom of the ice bin.

Units with Cold Plates include a soda line chase at top of splash on right & left ends of ice bin.

MECHANICAL:

Includes K-52 deck mount gooseneck spout faucet.

Faucet meet federal lead free standards.

1" IPS drains (sink bowl, recessed drainboard and ice bin).

1/2" IPS drain (ice bin with cold plate only).

15 amp. - 120V duplex receptacle.

ltem #:	Qty #:	
Model #:		
Project #:		

STAINLESS STEEL

26" Wide

Uni-Serv Speed Bars 🕨



15A - 120V GFI Duplex Receptacle Hidden Beneath Blender Shelf

LISTED

Conforms To NSF 61/9 Lead Free Requirements

MATERIAL:

22 gauge, 300 stainless steel

Sink Bowl: 20 gauge, 300 stainless steel

Understructure: 22 gauge galvaneal front/back; 11 gauge electrogalvaneal leg channel

Legs: 1 5/8" O.D. 18 gauge, galvanized steel with adjustable plastic bullet feet

Ice Bin Insulation: 2 lbs. density styrofoam (non-cold plate models); 2 lbs. density foam-in-place (cold plate models)

Cold Plate: Cast aluminum with 7 circuits (5 syrup and 2 water lines) with 5/16" diameter stainless steel bump and swedge ends.

OPTIONAL:

K-316-LU - Add wrist handles

SU-10A - 18" stainless steel leg upgrade with cross-bracing **SU-10C** - 14" stainless steel leg upgrade with cross-bracing

Model #	Overall Length	Ice Bin Capacity	Ice Bin Location	Approx. Weight	Approx. Cu. Ft.
CRU-60L	60"	98 lbs.	Left	110 lbs.	23
CRU-60R	60"	98 lbs.	Right	110 lbs.	23

With 7-Circuit Cold Plate

CRU-60L-7	60"	98 lbs.	Left	193 lbs.	23
CRU-60R-7	60"	98 lbs.	Right	193 lbs.	23

L And R Indicate Ice Bin Location

🔥 WARNING: Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 7:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication[™] Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

DIMENSIONS and SPECIFICATIONS

TOL Overall: ± .500" Interior: ± .250"

ALL DIMENSIONS ARE TYPICAL



