# SANDWICH UNIT REFRIGERATOR

## Model: SW48N12C-FB

Natural Refrigerant R-290 Model

### 48" Cutting Top Sandwich Unit Refrigerator with Solid Door - 12 Pans Front Breathing

Stainless steel front, top and end panels, aluminum back and interior.



### **Options and Accessories**

(upcharge and lead times may apply)		
Stainless steel interior	Flat lid	
Stainless steel back	Vision panel lid	
Additional epoxy coated steel shelves	Rear mounted cutting board	
Stainless steel shelves	Composite cutting board	
Overshelves (single or double)	Door locks	
Drawers in lieu of door(s)*	Modified pan opening	

Consult factory for other model configurations, options and accessories. \*Drawers hold (1) 1/2 x 6 pans & (1) 1/3 x 6 pan per drawer





Project Name:	
Model Specified:	
Location:	
Item No:	Quantity:
AIA #:	SIS #:

### **Standard Model Features**

#### **REFRIGERATION SYSTEM**

Performance rated refrigeration system
Natural, environmentally safe, high efficiency R-290 refrigerant <sup>1</sup>
Unique air flow distribution allows pan product to maintain 33° - 41°F
Automatic, hot gas condensate evaporator
Non-corrosive, plasticized fin evaporator coil
Easily serviceable, back mounted compressor
Expansion valve system

#### CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation
Smooth, polished chrome door handles
Spring loaded, self closing doors
Magnetic snap in Santoprene™ door gaskets
Heavy duty, epoxy coated steel shelves
19" deep, full length nylon cutting board
Insulated lid
Completely enclosed, vented and removable case back
3 3/4" casters

#### **MODEL FEATURES**

(12) $1/6$ size recessed pans, 4" deep
Electronic control, off-cycle defrost
Removable interior tub below pans
Field rehingeable doors

<sup>1</sup> R-290 refrigerant meets all federal and state regulatory requirements.

Front breathers are a unique, field assembled, bottom mounted ventilation system designed to allow cabinets to be flush against a wall or built into a counter to conserve space. For proper operation, the area under and in front of the cabinet <u>must</u> not be obstructed in any way.

**APPROVAL:** 

## **Model Specifications**

## **Model Plan Views**

DIMENSIONAL DATA	
Net Capacity (cubic feet)	13.4 (379 cu l)
1/6 Size Pans (4" deep)	12
Width, Overall (inches)	48 (1219 mm)
Depth, Overall (inches) (including cutting board & bumpers)	38 1/4 (972 mm)
Depth, Cutting Board (inches)	19 (483 mm)
Height, Overall (inches) (including 3 $3/4$ " casters)	41 (1041 mm)
Shelf Area (square feet)	6.8 (0.6 sq m)
Number of Shelves	2
Number of Doors	2
Interior Depth (inches)	See Drawing
Interior Height (inches)	26 1/4 (667 mm)
Interior Width (inches)	44 (1118 mm)

#### **REFRIGERANT DATA**

Condensing Unit Size (H.P.)	
Capacity (BTU per hour)*	

#### **ELECTRICAL DATA**

Voltage (International)	115/60/1 (220/50/1)
Total Amps (International)	4.8 (2.7)
10 ft. Cord/Plug [attached] (International)	Yes (No)

1/4

1940

#### **SHIPPING DATA**

Weight (pounds)	315 (143 kg)
Height - Crated (inches)	43 1/4 (1099 mm)
Width - Crated (inches)	56 (1422 mm)
Depth - Crated (inches)	37 1/4 (946 mm)

\* Rating @ +25°F evaporator, 90°F ambient Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.







