




# POWER PACK - AIR COOLED

PREMIUM - 4 PUMP - 11,500 BTUs

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Exterior sight glass to verify glycol bath level.
- Anti-vibration pads reduce motor noise.
- Rugged stainless steel cabinet.




**MMPP4307-PKG-4**



6-20P



| Part No.   | Description                             | Shipping Weight   |
|--|---|-------------------|
|  MMPP4307-PKG-4 | Air cooled power pack, 4 pump and motor | 134 kg<br>295 lbs |

Operating Performance

|                    |          |                              |                           |
|--------------------|----------|------------------------------|---------------------------|
| Compressor         | 1 1/2 HP | Charge                       | 1.04 kg (37 oz)           |
| BTU per hour       | 11,500   | Refrigerant Running Pressure | 55 (low) 260 (high)       |
| Plug Type (NEMA #) | 6-20P    | Bath Capacity                | 43.5 litre (11.5 gallons) |
| Voltage            | 208/230  | Pump Type                    | Rotary Vane               |
| Running            | 14.5A    | Pump & Motors                | 4                         |
| Refrigerant        | R-404A   | Pump Motor                   | 1/3 HP                    |
|                    |          | Push In Connector            | 12.7mm (1/2") O.D.        |

Dimensions

