

Refrigeration Equipment 12-Crate Milk Cooler 50" Long

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



738276 (KCHMC49)

12-Crate Milk Cooler 50" Long

Short Form Specification

Item No.

School milk cooler with exterior back panel in white-painted steel, bottom panel in galvanized steel, exterior side panels in white-painted steel and top in 430 stainless steel; interior back and side panels in 430 stainless steel, interior bottom in 304 stainless steel. Interior drain and electronic temperature control.

Heavy duty locking casters, removable door gasket, lid and key to protect the unit.

R290 gas in the refrigeration circuit.

ETL Safety and Sanitation certified.

3/5 Years warranty.

Main Features

- External temperature display.
- Removable gasket for easy cleaning operations.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Cabinet completely insulated with high density polyurethane for low environmental impact.

Construction


- Heavy-duty, locking casters keeps the unit in place but allow position adjusting.
- Locking lid to protect contents of the unit.
- Internal drain for easy clean out.
- Pre-wired heavy duty power cord.
- · Cold Wall evaporator.

Sustainability

- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane).
 Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.



Refrigeration Equipment 12-Crate Milk Cooler 50" Long



Electric

Supply voltage:

738276 (KCHMC49) 115 V/1 ph/60 Hz

Electrical power, max: 0.21 kW

Plug type: USA NEMA 5-15P

Capacity:

Gross capacity: 18 cu.feet

Key Information:

49 1/32" (1245 mm) **External dimensions, Width:** External dimensions, Depth: 30 9/16" (777 mm) External dimensions, Height: 42 1/64" (1067 mm) Internal Dimensions (depth): 26 1/2" / (673.1 mm) Internal Dimensions (height): 25 1/2" / (647.7 mm) 45 11/16" / (1160.78 mm) Internal Dimensions (width): Shipping height: 48 5/8" (1235 mm) Shipping weight: 282 lbs (128 kg) Shipping volume: 46.13 ft³ (1.31 m³) Type of external material: Prepainted white Type of internal material: Stainless Steel Warranty: 3 / 5 years

Approvals ETL C&US;ETL SANITATION

Refrigeration Data

Compressor power: 1/3 hp
Operating temperature min.: 35.6 °F
Operating temperature max.: 37.4 °F
Condenser type: Fin & tube
Defrost type: Auto Defrost

Sustainability

Current consumption:3 AmpsRefrigerant type:R290GWP Index:3Refrigerant weight:90 g









