

**MODEL: IMD-EVV70**

*Wine Cellars*



#### GENERAL FEATURES

*Elevate your wine experience with our meticulously designer refrigerators. Precise temperature control for red, white, rosé, and brut wines. Protect your collection with UV-resistant glass or solid doors.*

- ✓ **Doors.** Self-closing door system features a permanent pressure mechanism, ensuring a secure closure every time. Additionally, a convenient 'stay open' feature engages when the door remains open at 95 degrees or beyond. Our doors also include triple chamber door gaskets that are easy to remove and snap in, ensuring an effective seal.
- ✓ **Control System.** Our temperature management system offers unparalleled precision, allowing for highly accurate temperature settings. With greater flexibility in adjusting temperature ranges, our system can be tailored to meet the unique needs of each end user. This ensures optimal performance and maximum satisfaction with every use.
- ✓ **Lighting.** LED lighting in the canopy and cabinet sides reduces the energy consumption by 80% to 90% compared to a traditional bulb, better light quality.
- ✓ **100% Tested.** All condenser units are 100% tested, in helium chambers for refrigerant leak detections.
- ✓ **Certified.** Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7.



Rev:02 Date: 09/23/2023 IMD-EVV70

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE

**MODEL: IMD-EVV70**

**Wine Cellars**

**STANDARD FEATURES**

> **Exterior**

-Black lacquered steel.

> **Interior**

-Plastic-coated steel, grey.

-LED lighting.

> **Door**

-Double pane glass door, with self-closing system, opening lock double low emissivity Thermopane low emissivity thermopane. Magnetic weatherstripping.

-Door lock.

> **Insulation**

-CFC- Free polyurethane insulation, entire cabinet structure is foamed-in using a high-density polyurethane insulation.

-Low GWP & Zero ODP effect.

> **Shelving**

- (6) six plastic coated steel shelves, adjustable and easy removal.

- Dimensions WxD: 15-47/64" x 18-7/64" (400x460 mm).

> **Refrigeration**

- Digital temperature controller with automatic defrost system,

- Evaporative pan,

- Evaporator coil coated with anti-corrosion material 100% Polyester.

- Forced air refrigeration system,

**Refrigeration capacity:**

**IMD-EVV70 – 1263 Btu/h(14°F)/370 W(-10°C).**

> **Temperature**

- A single temperature (from 39°F (4°C) to 64°F (18°C)) and appropriate humidity (50% to 70%),

- Recommended temperature, Red Wine between 50°F (10°C) to 64°F (18°C) / White, Rosé and brut between 39°F (4°C) to 46°F (8°C).

> **Electrical**

- Cord and NEMA 5-15P plug.

- Electrical connection is 115V / 1ph / 60 Hz.

- 15 AMP breakers required.



> **ETL Listed to UL471 Standard and Sanitation classified to NSF7.**

**OPTIONAL FEATURES**

✓ Additional shelves.

✓ Electrical connection is 230 V / 1 ph / 50 Hz (Plug type varies).

Model;

- IMD-EVV70: 1,98 A.

Rew:02 Date: 09/23/2024 IMD-EVV70

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE

