



**BEVERAGE-AIR**

Project: _____	AIA#
Item: _____	
Location: _____	SIS#
Approved: _____	

**PFT2HC TOP MOUNT ROLL-THRU FREEZER**

**P SERIES TOP MOUNT ROLL-THRU FREEZER**  
**PFT2HC Solid Door Freezer**  
**Hydrocarbon Series**

**MODEL:**  
**PFT2HC-1AS**



**7 Year Parts/Labor Warranty**  
**7 Year Compressor Warranty**

**CABINET CONSTRUCTION**

- Exterior stainless steel front and side (galvanized top, bottom)
- Interior is made of corrosion resistant aluminum
- Full electronic control
- Expansion valve technology
- Variable speed compressor technology
- Self-closing door with 120° stay-open feature
- Stainless steel door liners
- 22 Gauge stainless steel doors
- LED interior light
- Heavy-duty cylinder locks
- Snap-in magnetic gaskets for positive door seal
- Hinged front shroud
- Reinforced stainless steel door ramps
- Internal cart guides
- Accepts carts up to 26 3/8" (W) x 26" (D) x 64 1/2" (H) (cart not included)
- Wiper gasket at bottom of door seals door to ramp
- Energy saving thermal breaker
- Stainless steel breaker caps
- 8' Cord and plug (see electrical data for details)

**OPTIONS & ACCESSORIES**

- Stainless steel interior
- Door swing orientation (at time of order)

**REFRIGERATION SYSTEM**

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Adaptive defrost
- Epoxy coated evaporator coil, located out of the food zone
- Freezer capable of maintaining product temperature down to -10°F



Please verify qualifying units by visiting:  
[www.energystar.gov/cfs](http://www.energystar.gov/cfs)

3779 Champion Blvd., Winston-Salem, NC 27105  
1-888-845-9800 Fax: 1-336-245-6453  
Beverage-Air.com Sales@bevair.com



# BEVERAGE-AIR®

MODEL	PFT2HC-1AS
<b>EXTERNAL DIMENSIONAL DATA</b>	
Width Overall	68 <sup>7</sup> / <sub>8</sub> "
Depth Overall with Handle	39 <sup>7</sup> / <sub>8</sub> "
Height Overall	84 <sup>3</sup> / <sub>8</sub> "
Number of Doors	4
Between Cart Guides	26 <sup>3</sup> / <sub>4</sub> "
Depth with Doors Open 90°	98 <sup>1</sup> / <sub>4</sub> "
Door Openings (in)	27 <sup>7</sup> / <sub>8</sub> " x 65 <sup>1</sup> / <sub>2</sub> "
<b>INTERNAL DIMENSIONAL DATA</b>	
NET Capacity (cubic ft.)	78.5
Internal Width Overall (in)	63 <sup>5</sup> / <sub>8</sub> "
Internal Depth Overall (in)	26"
Internal Height Overall (in)	66 <sup>1</sup> / <sub>4</sub> "
<b>ELECTRICAL DATA</b>	
Full Load Amperes 115/60/1*	13.9
<b>REFRIGERATION DATA</b>	
Horsepower	(2) 3/4
Capacity (BTU/Hr)	4900
Heat Rejection (BTU/Hr)	7350
Charge (lbs/grams/ounces)	0.2866 / 130 / 4.6
<b>SHIPPING DATA</b>	
Gross Weight (crated lbs)	735 lbs
Height - Crated	92"
Width - Crated	78"
Depth - Crated	45"

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).

## P Series Top Mount Roll-Thru Freezer Model: PFT2HC-1AS

**Model Views**

Required Clearance: Top 12"

**PLAN VIEW**

**ELEVATION VIEW**

**SIDE VIEW**

### ELECTRICAL CONNECTION



115/60/1\*  
NEMA 5-15P

Unit pre-wired at factory  
and include 8' long cord  
and plug set.

\* NOTE: Units that utilize variable speed compressor technology can experience nuisance tripping on Class A GFCI outlets which have a trip limit of 4 to 6 mA. To avoid this issue in a location that requires GFCI circuit protection, Beverage-Air recommends using either an Eaton, SCF20, or HUBBELL Model Number GFRST83W 20A Heavy Duty Hospital Grade Self-Test GFCI Receptacle.

