

Project:	AIA#
ltem:	
Location:	SIS#
Approved:	

## DRAFT BEER EQUIPMENT-DIRECT DRAW DISPENSER

DD24HC Solid Door Single Tower With Faucet Hydrocarbon Series

MODEL: DD24HC-1-S



7 Year Parts/Labor Warranty 7 Year Compressor Warranty

#### **CABINET CONSTRUCTION**

- Exterior stainless steel with galvanized steel back
- Top is made from heavy-duty stainless steel including drip tray
- Interior is galvanized steel on walls and ceiling, reinforced floor and doorsill are heavy-duty stainless steel
- Mechanical control
- Single tower with faucet
- 3-in-1 Draft solution uses a single stainless-steel tap to serve different beverages, such as wine, beer, and coffee (or other non-alcoholic beverages) through silver-lined, anti-microbial tubing that is 100% effective against the top 4 beverage spoiling bacteria
- 3" Stainless steel insulated dispensing tower
- Drain tube located at bottom front of cooler for connection to floor drain
- Four-inch (4") heavy duty casters standard
- Door lock
- Self-closing door with 120° stay-open feature
- · Magnetic gaskets provide positive door seal
- Field reversible door (hinge kit not included)

#### **OPTIONS & ACCESSORIES**

- · Stainless steel interior lining
- Stainless steel back
- Wine/coffee models
- Glass door
- Faucet locks
- Glass rinser
- · Right or left hinged door
- Sub-top
- No draft arm/hole cover
- 1- 4 Tap tower
- 2, 3 & 4 way manifolds
- · Dial/digital thermometer

### **REFRIGERATION SYSTEM**

- Refrigeration system uses R290 refrigerant to comply with all environmental concerns
- · Automatic, non-electric defrost
- Epoxy coated evaporator coil
- Maintains product temperatures between 36°F and 38°F










MODEL	DD24HC-1-S	
EXTERNAL DIMENSIONAL DATA		
Width Overall	24"	
Depth Overall	30 1⁄8"	
Height Overall (floor to top of tap)	53"	
Number of Doors	1	
Depth with Door Open 90°	50 ¾"	
Door Openings (in)	19 ¾" x 28"	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	7.66	
Internal Width Overall (in)	20"	
Internal Depth Overall (in)	22 1⁄4"	
Internal Height Overall (in)	23 ½"	
Number of 1/2 Kegs	1	
ELECTRICAL DATA		
Full Load Amperes	2.0	
REFRIGERATION DATA		
Horsepower	1/6	
Capacity (BTU/Hr)	1094	
Heat Rejection (BTU/Hr)	1641	
Charge (lbs/grams/ounces)	0.1213 / 55 / 1.94	
SHIPPING DATA		
Gross Weight - Crated	184 lbs	
Height - Crated	46"	
Width - Crated	32"	
Depth - Crated	27"	

\*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.


We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).



# Bar Equipment-Direct Draw Beer Dispenser Model: DD24HC-1-S









115/60/1 NEMA 5-15P Unit pre-wired at factory and include 8' long cord and plug set.

