

Project	
ltem #	
Quantity	

ARSHP HOT PLATE

GAS TYPE:

NATURAL

LF



ARSHP-12-2 ARSHP-24-2

ARSHP-24-4 ARSHP-36-3

ARSHP-36-6 ARSHP-48-4

ARSHP-48-8 ARSHP-60-10

STANDARD FEATURES

- Two piece lift off 32,000 BTU/hr. burners
- Heavy duty removable, 12" x 12"cast-iron grates
- · Manual gas control valve for each burner
- Stainless steel pilots for instant ignition on each burner
- Full-width removable stainless steel crumb tray for easy cleaning
- 4" adjustable inset legs (12" to 48" models)
- · Die-cast, red control knob
- Available in several widths from 12", 24", 36", 48", and 60"
- 4" back riser
- · Two year limited warranty, parts, and labor

OPTIONAL FEATURES

- · Stainless steel stands
- · Casters for stands



Model Shown ARSHP-36-6

DESCRIPTION

Gas Hot Plate American Range No._____.

ARSHP series comes in a variety of burner configurations single depth or double depth. Low profile gas hot plate.

Stainless steel front, sides and front top ledge. Unit height 12 9/16" with 4 " adjustable legs. Each burner is a individually controlled 32,0000 BTU/burners, two piece lift off burners head for ease of cleaning and a 12" x 12" cast iron grate. Standing pilot ignition system. 3/4" rear gas connection natural gas or LP. Two year limited warranty for parts and labor.











ARSHP HOT PLATE


TOP





FRONT











COUNTERTOP	BURNERS	WIDTH (MM)	DEPTH (MM)	HEIGHT (MM)	BTU/hr.	LBS
ARSHP12-2	2	12" (305)	30" (762)	12" 9/16 (319)	64,000	95
ARSHP24-2	2	24" (610)	18" (458)	12" 9/16 (319)	64,000	95
ARSHP 24-4	4	24" (610)	30" (762)	12" 9/16 (319)	128,000	145
ARSHP-36-3	3	36" (914)	18" (458)	12" 9/16 (319)	96,000	115
ARSHP-36-6	6	36" (914)	30" (762)	12" 9/16 (319)	192,000	210
ARSHP-48-4	4	48" (1219)	18" (458)	12" 9/16 (319)	128,000	140
ARSHP-48-8	8	48" (1219)	30" (762)	12" 9/16 (319)	256,000	270
ARSHP 60-10	10	60" (1524)	30" (762)	12" 9/16 (319)	320,000	325

	MANIFOLD PRESSURE NATURAL GAS PROPANE GAS MANIFOLD SIZE					
I	5.0" W.C.	10.0" W.C.	3/4" (19MM)			

- Specify type of gas and altitude if over 2000 feet.
- Please specify gas type when ordering.

Subject to change without notice

*Shipping weight includes packaging and is approximate.

COMBUSTIBLE WALL CLEARANCES:

For use only on non-combustible floors. Legs or casters are required, or 2" (51) overhang is required when curb mounted. Clearance from non-combustible walls is 0". When unit is placed next to combustible walls, clearances must exceed 12" (305) from sides, and 4" (102) from rear.

Commercial cooking equipment requires an adequate ventilation system. For additional information, refer to the National Fire Protection Association's standard.

NFPA96 "Vapor Remocal from Cooking Equipment." (NOTE: For North America only)





