

# REACH-IN FREEZER (0°F)

## Model: 2FSNHD

Natural Refrigerant R-290 Model

### 2-Section Reach-In Freezer with Half Doors - Shallow Depth

**2FSNHD** - Stainless steel front, aluminum end panels and interior  
**2FSNSAHD** - Stainless steel exterior, aluminum interior  
**2FSNSSHD** - Stainless steel exterior and interior



## Options and Accessories

(upcharge and lead times may apply)

|   |  |
|---|--|
| Stainless steel case back                         | Standard depth (consult factory)   |
| Additional epoxy coated steel shelves             | Hinged glass doors (consult factory)   |
| Chrome or stainless steel shelves                 | Full doors   |
| Heavy duty pilaster strips                        | Rehinging of doors (consult factory)   |
| Wine rack   | <b>Correctional Facility Options</b>   |
| Adjustable legs                                   | <ul style="list-style-type: none"> <li>One way security screws</li> </ul>                              |
| Custom laminates                                  | <ul style="list-style-type: none"> <li>Locking hasp (lock not included)</li> </ul>                     |
| Special electrical requirements (consult factory) | <ul style="list-style-type: none"> <li>Stainless steel mesh cover</li> <li>Coverless hinges</li> </ul> |

Consult factory for other model configurations, options and accessories.

**Continental**<sup>®</sup>  
Refrigerator



Project Name:

Model Specified:

Location:

Item No:

Quantity:

AIA #:

SIS #:

## Standard Model Features

### REFRIGERATION SYSTEM

Self contained, performance rated refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant<sup>1</sup>

Automatic, electric condensate evaporator

Expansion valve system

Standard operating temperature is 0 to -5°F and can be adjusted to operate as low as -10°F in a 90°F ambient.

### CABINET ARCHITECTURE

3" non-CFC polyurethane foam insulation

Smooth, polished chrome workflow door handles

Cam action, lift off hinges

Self-closing doors

Magnetic snap in Santoprene<sup>®</sup> door gaskets

Cylinder lock in each door

Heavy duty, epoxy coated steel shelves

5" casters

### MODEL FEATURES

LED interior lighting

Electronic control, automatic electric defrost

<sup>1</sup> R-290 refrigerant meets all federal and state regulatory requirements.

APPROVAL:

## Model Specifications

### DIMENSIONAL DATA

|  |                  |
|--|------------------|
| Net Capacity (cubic feet)                          | 32 (906 cu l)    |
| Width, Overall (inches)                            | 52 (1321 mm)     |
| Depth, Overall (inches)<br>(including handles)     | 29 1/4 (743 mm)  |
| Depth (inches) (less doors)                        | 25 7/8 (657 mm)  |
| Depth (inches) (doors open 90°)                    | 49 1/2 (1257 mm) |
| Clear Door Width (inches)                          | 19 3/8 (492 mm)  |
| Clear Half Door Height (inches)                    | 27 1/2 (699 mm)  |
| Height, Overall (inches)<br>(including 5" casters) | 82 1/4 (2089 mm) |
| Number of Doors                                    | 4                |
| Number of Shelves                                  | 6                |
| Shelf Area (square feet)                           | 40.8 (3.8 sq m)  |

### REFRIGERANT DATA

|                             |      |
|-----------------------------|------|
| Condensing Unit Size (H.P.) | 1/2  |
| Capacity (BTU per hour)*    | 2470 |

\* Rating @ -15°F evaporator, 90°F ambient

### ELECTRICAL DATA

|  |                     |
|--|---------------------|
| Voltage (International)                        | 115/60/1 (220/50/1) |
| Feed Wires (including ground)                  | 3                   |
| Total Amps (International)                     | 8.9 (4.1)           |
| Defrost Amps (International)                   | 6.1 (3.2)           |
| 10 ft. Cord/Plug [attached]<br>(International) | Yes<br>(No)         |

### SHIPPING DATA



|                              |                  |
|------------------------------|------------------|
| Height - Crated (inches)     | 85 1/2 (2172 mm) |
| Width - Crated (inches)      | 64 (1626 mm)     |
| Depth - Crated (inches)      | 42 (1067 mm)     |
| Volume - Crated (cubic feet) | 133 (3766 cu l)  |
| Weight Std - Crated (pounds) | 436 (198 kg)     |
| Weight SS - Crated (pounds)  | 524 (238 kg)     |

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug  
(varies by country)

## Model Plan Views



**IMPORTANT NOTE:** If the cabinet is located directly against a wall and/or under a low ceiling, a minimum clearance of 12" is required on top and 3" on sides and rear.

**Continental**  
Refrigerator

Toll-Free: 800-523-7138  
Phone: 215-244-1400  
Fax: 215-244-9579

539 Dunksferry Road  
Bensalem, PA 19020  
[www.continentalrefrigerator.com](http://www.continentalrefrigerator.com)

Due to our continued efforts in developing innovative products, specifications subject to change without notice.



PROUDLY  
DESIGNED & ASSEMBLED  
IN THE U.S.A.

**Intertek**

© Copyright 2021. Continental Refrigerator.  
A Division of National Refrigeration & Air Conditioning Products, Inc.

REVISED: 3/28/24