




POWER PACK - AIR COOLED

PREMIUM - 2 PUMP - 5,100 BTUs

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Exterior sight glass to verify glycol bath level.
- Anti-vibration pads reduce motor noise.
- Rugged stainless steel cabinet.



MMPP4303-PKG




6-20P*



*Units manufactured prior to 2/1/2022 were produced with a 6-15P plug.



Part No.	Description	Shipping Weight
 MMPP4303-PKG	Air cooled power pack, 2 pump and motor	80 kg 175 lbs

Operating Performance

Compressor	3/4 HP	Refrigerant	R-134a
BTU per hour	5,100	Charge	0.79 kg (28 oz)
Plug Type (NEMA #)	6-20P*	Refrigerant Running Pressure	18 (low) 140 (high)
Cord Length	8'	Bath Capacity	43.5 litre (11.5 gallons)
Voltage	208/230	Pump Type	Rotary Vane
Running	9.5A	Push In Connector	12.7mm (1/2") O.D.

*Units manufactured prior to 2/1/2022 were produced with a 6-15P plug.

Dimensions

