

## Induction Cooker

C.A.C. Commercial Induction Cooker Series features SCHOTT CERAN® glass surface for optimal durability, temperature resistance and energy efficiency. Designed with German glass-ceramic technology, the glass surface is able to withstand sudden temperature shocks up to 1,380°F/750°C and intensive use of a busy commercial kitchen. Effectively concentrating the heat in a confined area of surface while keeping the rest of surface relatively cool, C.A.C. induction cooker helps achieve cooking safety and energy saving.



### High-Power Commercial Induction Cooker

- The appliance beeps as a safety alert if the glass surface does not detect a suitable induction-ready cookware.
- ETL listed; meets and complies with electrical safety standards in the U.S.A. (UL-197)
- One-year warranty



Item	Description	UOM	Case
ELIC-1200G	3500W, 240V	Each	1/2

### Commercial Induction Cooker

- The appliance beeps as a safety alert if the glass surface does not detect a suitable induction-ready cookware.
- ETL listed; meets and complies with electrical safety standards in the U.S.A. (UL-197)
- ETL sanitation listed; complies with NSF/ANSI-4
- One-year warranty



Item	Description	UOM	Case
ELIC-600G	1800W, 120V	Each	1/2



ELIC-600G



 Check full line of induction-ready cookware on page 86.

#### ■ SPECIFICATIONS

	ELIC-600G	ELIC-1200G
Dimensions	12-5/8" L x 16-1/2" W x 3-7/8" H	12-5/8" L x 16-1/2" W x 3-7/8" H
Voltage	120V	240V
Power	1800W	3500W
Frequency	60Hz	60Hz
Plug Type	NEMA 5-15P	NEMA 6-20P
Shipping Dimensions	15" x 5-1/2" x 18-3/4" H	15" x 5-1/2" x 18-3/4" H
Shipping Weight	14 lbs	14 lbs