DISHWASHERS





Models: 1510 / 500

Standard Features

- 304 Stainless Steel Handle and Body
- High Temp with Booster
- IP 44 Washing Pump: Peristaltic Rinse Aid & Detergent Pump
- Self Cleaning function
- 3 Washing Programs
- Malfunction Self-Diagnose
- Automatic Draining Pump
- Thermo-protector feature
- Standard Pressure Reducer Valve (PRV)
- Tank & Boiler Thermometer

<u>1510</u>

- Capable of washing GN 1/1 pan
- Stainless-Steel Washing Nozzles

<u>500</u>

- Steady Upper Washing Nozzles for more efficiency
- Stainless-Steel Wash & Rinse Group





1-year parts and labor warranty (US Only)

performance and equipment

longevity.



1510 (Open)

н

н

	SPECIFICATIONS 1510	500	(
Motor Power (Hp)	1 1/2	3/4	
Туре	Door Uni∨ersal	Undercounter Front Loading	
Basket Dimension	20" × 20"	20" × 20"	
Door Clearance	15.75"	14.17"	
Length of Cycle	60/120/180 sec**	60/120/180 sec**	
Baskets/Hour	30	20/30/60 **	
Glasses/Hour	1470	735/1470/2205	
Dishes/Hour	540	270/540/810	
Tank Capacity	15 Gal (56.8 L)	9.2 Gal (35 L)	
Boiler Capacity	2 Gal (7.6 L)	1.6 Gal (6.1 L)	
Power Supply	220V/60HZ/1ph	220V/60HZ/1ph	
Power (kW)	8.6	3.6	
Amps	39.1	16.4	
Plug / Connection	Wire - No plug		Contraction (3)
Product Dim. (WxDxH) DOOR CLOSED	29.5" × 34.6" × 54.7"	22.4" × 23.6" × 32.7"	
Product Dim. (WxDxH) DOOR OPENED	29.5" × 34.6" × 72"	22.4" × 37.8" × 32.7"	
Product Weight (Ibs)	291	122	
Shipping Dim. (WxDxH)	30" × 36" × 61"	24" × 28" × 40"	D
hipping Weight (Ibs)	327	133	
*Depends on Progra	m Selection		
Notes: • Properly clean daily use to ens			



W

Δ

Connection

Direct Water Drain Required

Wired

No Plug

AMPTO is continuously improving products. Specifications are subject to change without notice.