

Slim Line Back Bar Refrigerators

SOLID DOORS
GLASS DOORS











As bar layouts are becoming increasingly smaller, refrigeration airflow is crucial to the success and operation of your unit. All Asber's bar Refrigerators are **fully front breathing** enabling them to be placed in the most compact environments for a seamless fit. **Complete side-mount refrigeration system** allows for full access to your products without the impedance of a roof mount evaporator giving you a worry-free operating environment.

Black vinyl is the preferred finish for Bar Equipment as its more durable and doesn't chip versus a painted finish. Asber's Bar Refrigerators come with a chip resistant black vinyl exterior finish front, sides and back. Interior walls with NSF approved white coated steel finish to enhance its merchantability, easy to clean with a sturdy stainless-steel floor. Always one step above to ensure the upmost in safety and sanitation for your establishment.

Insulation in any Refrigerator is one of the most important factors for thermal efficiency. Asber only uses the world's leader Ecomate (GWP) (ODP) insulation, 2" thick for the highest R value efficiency for your environments.

With innovative and eco-friendly technology, Asber utilizes **R-290 Hydrocarbon** designed to meet DOE's Energy Conservation standards with very low contribution to global warming (ODP-0) (GWP-3).

LED interior lights offer shadow-free illumination, which lasts up to 10 times longer than fluorescent lights to enhance product display.

Double pane, hinged GLASS DOOR REFRIGERATORS with argon gas insulation for enhance energy efficiency. Prevents heat transfers, minimizes condensation and provides a frost-free viewing environment.

Additional features to include:

- · Hermetic compressors with epoxy coated evaporator
- Automatic evaporator: Paper fins not utilized in the evaporation process.
- · Electronic controller.
- · LED interior lights.
- Temperature: Refrigerators 32°F to 38°F based on an external environment of 90°F and 65% RH.
- Door locks with universal key.
- Meets the NSF-7 standard for food safety



ABBC-24-48G



ABBC-24-60G



ABBC-24-72G

OPTIONS & ACCESORIES

Additional 2nd year warranty. 2.5" castors. Additional epoxy coated shelves. Voltage: 220V. - I - 50Hz. 6" adjustable stainless-steel legs.



•	•									
MODEL	DOORS	SHELVES	CAPACITY (12 oz. can)	AMPS	НР	VOLTS	Width	DIMENSIONS Depth	Height ¹	SHIPPING WEIGHT (lbs)
ABBC-24-48	2	4	300	2.0	1/4	115/60	49 5/8"	24 3/8"	35 1/2"	250
ABBC-24-60	2	4	390	2.0	1/4	115/60	62 1/4"	24 3/8"	35 1/2"	305
ABBC-24-72	3	6	540	2.0	1/4	115/60	72"	24 3/8"	35 1/2"	370
ABBC-24-48G	2	4	300	2.0	1/4	115/60	49 5/8"	24 3/8"	35 1/2"	270
ABBC-24-60G	2	4	390	2.0	1/4	115/60	62 1/4"	24 3/8"	35 1/2"	325
ABBC-24-72G	3	6	540	2.0	1/4	115/60	72"	24 3/8"	35 1/2"	400



Slim Line Back Bar Coolers

SOLID DOORS **GLASS DOORS**


























COMMON TOP VIEW

ELECTRICAL DATA	24-48		24-60		24-72			
ELECTRICAL DATA	Solid	Glass	Solid	Glass	Solid	Glass		
Voltage	115/60							
Plug Type	Nema 5-15P							
Full Amp. Loads	2.0							
Compressor HP	1/4							
Cord Length (ft)	10							
Refrigerant	R-290							

Refrigerant	R-290							
DIMENSIONAL DATA								
# of Doors		4	6					
Capacity (12 oz. can)	300		39	390		540		
Ext. Width Overall	49	5/8"	62 1/4"		72"			
Ext. Depth Overall	24 ³ /8"							
Ext. Height Overall	35 1/2"							
Int. Width Overall	36 1/4"		48 7/8"		58 ³ /4"			
Int. Depth Overall	18 1/2"							
Int. Height Overall	29 1/4"							
# of Shelves		4	6					
Shelf Size (L x D)	21 5/8" :	x 22 ½"	26 5/8"	x 22 ½"	22 ½" x 18 5/8" 22 ½" x 21 5/4" 22 ½" x 23 ½"			
Shipping Weight (lbs.)	250	270	305	325	370	400		

Standard Features

- 2" Ecomate CFC Free foam in place insulation.
- Electronic controller with digital display.
- LED interior lights.
- Self-contained Refrigeration with epoxy coated evaporator.
- Door locks with universal key.
- Meets the NSF-7 standard for food safety.

Options & Accesories

- Additional 2nd year warranty.
- 2.5" castors Set of 4, front 2 with brakes.
- Additional epoxy coated shelves.
- Voltage: 220V. 1 50 hz.
- 6" adjustable stainless-steel legs.

Warranty

- · 1-year parts & labor.
- 5-year compressor.

*RESIDENTIAL APPLICATIONS: Asber assumes no liability for parts or labor coverage for component failure, factory defect or any other damages for units installed in noncommercial foodservice or residential applications.