

Project: \_\_\_\_\_ Location: \_\_\_\_\_ Item #: \_\_\_\_\_ Quantity: \_\_\_\_\_

## Standard Features

- Kettle System-Seamless deep-drawn 316 kettle liner (up to 40 gal, 304 liner for 40+ gallon) with an integrally formed radius lip
- 304 stainless kettle jacket
- Kettle protection system— thermostat temperature control, 150°F - 260°F, pressure relief valve, air eliminator valve, pressure gauge, jacket-water fill, automatic low water cut off and indicator light, field replaceable heating elements, tilting cut-off switch
- Full body insulation between kettle jacket and outer casing
- 304 stainless outer casing seam welded to radius lip
- 304 stainless, seam welded to control console
- 304 stainless, reinforced gear box
- Self locking worm gear tilt mechanism
- 304 stainless, 2" tubular support frame
- Adjustable flanged feet

## Optional Features

- Single or dual faucet with bracket & 12" or 18" swing nozzle\*
- 60" flexible spray hose assembly (vinyl or stainless) for dual or single faucet\*
- Faucet bracket (ALFBT)
- Riser for table mounted fill faucet (ALRISER)
- Automatic water filling meter (ALACWS)
- Mixer/agitator, two speed (Call for pricing)
- Correctional Package\*
- 316 Liner (AL316LNR)

\* Call AccuTemp for additional information

## Electrical Options

208V, 240V, 380V, 415V, 440V, 480V

## Short Spec

AccuTemp Edge Series tilting floor-mounted kettle, model ALTWE-XX (20, 30, 40, or 60 gallon capacity), seamless deep-drawn 316 kettle liner (up to 40 gal, 304 liner for 40+ gallon) with integrally formed radius lip and 304 stainless kettle jacket. Full body insulation between the kettle jacket and outer casing. 2/3 jacketed with pressure relief valve, pressure gauge, jacket-water fill valve, automatic low water cut off and indicator light and field replaceable heating elements. Seam welded control console with thermostat temperature control, 150°F to 260°F (65°C to 140°C).

## Other Approvals



## Accessories

- Care Kit (ALKCK-L)
- Electric timer with buzzer (ALAT)
- Pour lip pan holder assembly (ALPHKTL)
- Measuring strip (ALMS)
- Lift-off or two piece hinged\*
- 1 piece actuator-assisted lid, 20-60 gal. (ALACT-M)
- Single basket 20-40 gal. (ALSBI-M)
- Tri-basket insert (ALTBI-S)
- Nylon bag insert with spreader ring (ALNBI)
- 2" or 3" draw off valve, compression or ball type fitting\*

\* Call AccuTemp for additional information



**Model ALTWE-60**  
(shown with optional 1 1/2 draw-off valve)

**INSULATED SELF-CONTAINED TILTING FLOOR-MOUNTED KETTLE- ALTWE**

20-60 GALLON CAPACITY—Electric, 2/3 Jacketed Insulated for Safety™ Deep Drawn Construction Tilting, Floor Mounted. Made in USA

**MODEL ALTWE ELECTRICAL SPECIFICATIONS (AMPERES PER LEG)**

| GAL | KW | 208 Volt |      | 240 Volt |      | 380 Volt |      | 415 Volt |      | 440 Volt |      | 480 Volt |      |
|-----|----|----------|------|----------|------|----------|------|----------|------|----------|------|----------|------|
|     |    | 1Ø       | 3Ø   | 1Ø       | 3Ø   | 1Ø       | 3Ø   | 1Ø       | 3Ø   | 1Ø       | 3Ø   | 1Ø       | 3Ø   |
| 20  | 12 | 57.7     | 33.3 | 50.0     | 28.9 | 31.6     | 18.2 | 28.9     | 16.7 | 27.3     | 15.7 | 25.0     | 14.4 |
| 30  | 24 | 115.4    | 66.6 | 100.0    | 57.7 | 63.2     | 36.5 | 57.8     | 33.4 | 54.5     | 31.5 | 50.0     | 28.9 |
| 40  | 24 | 115.4    | 66.6 | 100.0    | 57.7 | 63.2     | 36.5 | 57.8     | 33.4 | 54.5     | 31.5 | 50.0     | 28.9 |
| 60  | 36 | 173.1    | 99.9 | 150.0    | 86.6 | 94.7     | 54.7 | 86.7     | 50.1 | 81.8     | 47.2 | 75.0     | 43.3 |

**MODEL ALTWE DIMENSIONS**

| GAL | A    | B    | C    | D   | F    | G    | H*   | K    | L    | S*   | W    | Y    |
|-----|------|------|------|-----|------|------|------|------|------|------|------|------|
| 20  | 22.0 | 16.0 | 41.6 | 7.0 | 43.1 | 42.0 | 22.2 | 31.0 | 35.0 | 36   | 18.0 | 35.5 |
| 30  | 23.0 | 20.3 | 43.5 | 7.0 | 44.1 | 42.5 | 19.8 | 31.0 | 36.0 | 36   | 18.5 | 37.4 |
| 40  | 25.5 | 22.3 | 47.5 | 7.0 | 46.6 | 43.5 | 21.7 | 31.0 | 38.5 | 37.3 | 19.9 | 41.4 |
| 60  | 29.5 | 48.6 | 48.6 | 7.0 | 51.6 | 45.3 | 19.9 | 31.0 | 42.6 | 39.3 | 21.9 | 42.5 |

\*Dimensions H & S apply only if an optional 2" draw-off is ordered. If a 3" draw-off is required, contact AccuTemp for applicable dimensions.

DRAWING REPRESENTS 60 GALLON MODEL WITH OPTIONAL 1 1/2" DRAW-OFF

