



# BEVERAGE-AIR

|                 |      |
|-----------------|------|
| Project: _____  | AIA# |
| Item: _____     |      |
| Location: _____ | SIS# |
| Approved: _____ |      |

**PRD1HC TOP MOUNT REFRIGERATOR: PASS-THRU**

## P SERIES TOP MOUNT REFRIGERATOR PASS-THRU

**MODEL:**  
PRD1HC-1AHS

PRD1HC Half-Solid Door Reach-In  
Hydrocarbon Series



**7 Year Parts/Labor Warranty**  
**7 Year Compressor Warranty**

### CABINET CONSTRUCTION

- Exterior stainless steel front and side (galvanized top, bottom & back)
- Interior is made of corrosion resistant aluminum
- Stainless steel door liner
- Full electronic control
- Expansion valve technology
- Variable speed compressor technology
- Self-closing doors with 120° stay-open feature
- 22 Gauge stainless steel pass-thru half doors
- LED interior light
- Cylinder locks
- Snap-in magnetic gaskets for positive door seal
- Hinged front shroud
- Energy saving thermal breaker
- Stainless steel breaker caps
- Three (3) heavy-duty epoxy wire coated shelves
- 6" High adjustable stainless steel legs
- 8' Cord and plug (see electrical data for details)

### OPTIONS & ACCESSORIES

- Stainless steel interior
- Additional shelves
- Shelf clips
- 3" or 6" Casters
- 6" Seismic legs
- Tray slides (type A & A/C)
- Door swing orientation (at time of order)
- Remote option\* (see note back on page)

### REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Adaptive defrost
- Epoxy coated evaporator coil, located out of the food zone
- Refrigerator capable of maintaining product temperature 36°F to 38°F



Please verify qualifying units by visiting:  
[www.energystar.gov/cfs](http://www.energystar.gov/cfs)

3779 Champion Blvd., Winston-Salem, NC 27105  
1-888-845-9800 Fax: 1-336-245-6453  
Beverage-Air.com Sales@bevair.com



# BEVERAGE-AIR®

| MODEL                            | PRD1HC-1AHS         |
|----------------------------------|---------------------|
| <b>EXTERNAL DIMENSIONAL DATA</b> |                     |
| Width Overall                    | 26 1/2"             |
| Depth Overall with Handles       | 38 3/8"             |
| Height Overall                   | 84 1/8"             |
| No. of Doors                     | 4                   |
| Depth with Door Open 90°         | 83 7/8"             |
| Door Openings                    | 21 1/2" x 25 1/4"   |
| <b>INTERNAL DIMENSIONAL DATA</b> |                     |
| NET Capacity (cubic ft.)         | 22.9                |
| Internal Width Overall (in)      | 22 1/2"             |
| Internal Depth Overall (in)      | 26"                 |
| Internal Height Overall (in)     | 56 3/8"             |
| No. of Shelves                   | 3                   |
| <b>ELECTRICAL DATA</b>           |                     |
| Full Load Amperes 115/60/1**     | 6.5                 |
| <b>REFRIGERATION DATA</b>        |                     |
| Horsepower                       | 1/3                 |
| Capacity (BTU/Hr)                | 2800                |
| Heat Rejection (BTU/Hr)          | 4200                |
| Charge (lbs/grams/ounces)        | 0.3307 / 150 / 5.29 |
| <b>WEIGHT DATA</b>               |                     |
| Gross Weight - Crated            | 425 lbs             |
| Height - Crated                  | 88"                 |
| Width - Crated                   | 35"                 |
| Depth - Crated                   | 45"                 |

\*NOTE: Remote units are field wired and come with 6" legs.  
Refrigerant must be specified at time of order.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).

## P Series Top Mount Refrigerator: Pass-Thru Model: PRD1HC-1AHS

**Model Views**

Required Clearance: Top 12"

**PLAN VIEW**

**ELEVATION VIEW**

**SIDE VIEW**

### ELECTRICAL CONNECTION



115/60/1\*\*  
NEMA 5-15P

Unit pre-wired at factory  
and include 8' long cord  
and plug set.

\*\* NOTE: Units that utilize variable speed compressor technology can experience nuisance tripping on Class A GFCI outlets which have a trip limit of 4 to 6 mA. To avoid this issue in a location that requires GFCI circuit protection, Beverage-Air recommends using either an Eaton, SCF20, or HUBBELL Model Number GFRST83W 20A Heavy Duty Hospital Grade Self-Test GFCI Receptacle.

