

Refrigeration Equipment 2-Drawer Under Counter Refrigerator 27" Long 32" Tall

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



738337 (KCHUC27.2DR-32)

2-Drawer Under Counter Refrigerator 27" Long 32" Tall

Short Form Specification

Item No.

2-drawer refrigerator counter top, 32 inch tall, with exterior back panel, exterior bottom panel, and exterior top panel in galvanized steel, exterior side panel in 430 stainless steel; interior back, top and bottom panels in 304 stainless steel. Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and temperature control. Vinyl heavy duty adjustable, easy to handle and clean shelves.

External temperature display. R600a gas in refrigeration circuit.

ETL Safety and Sanitation certified.

3/5 Years warranty.

Main Features

- External temperature display.
- · Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Cabinet completely insulated with high density polyurethane for low environmental impact.
- ADA Height Compliant

Construction

- Stainless steel interior and exterior, durable and easy to clean for daily commercial use.
- Heavy duty casters.
- Pre-wired heavy duty power cord.
- Magnetic gasket removable without tools for easy cleaning.
- Heavy duty drawer runners.

Sustainability

- CFC and HCFC free (ecological refrigerant type: R600a).
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.

Optional Accessories


• 1 ADJUSTABLE FOOT


PNC 206445 🗅

APPROVAL:




Refrigeration Equipment 2-Drawer Under Counter Refrigerator 27" Long 32" Tall





EI = Electrical connection



Electric

Supply voltage:

738337 (KCHUC27.2DR-32) 115 V/1 ph/60 Hz

Electrical power, max: 0.16 kW

Plug type: USA NEMA 5-15P

Capacity:

Gross capacity: 6.5 cu.feet

Key Information:

External dimensions, Width: 27 3/4" (705 mm) **External dimensions, Depth:** 29 15/16" (760 mm) **External dimensions, Height:** 32 1/16" (815 mm) Internal Dimensions (depth): 22 13/16" / (580 mm) Internal Dimensions (height): 23 1/2" / (597 mm) Internal Dimensions (width): 22 1/4" / (565 mm) Shipping height: 34 13/16" (885 mm) Shipping weight: 154 lbs (70 kg) Shipping volume: 18.62 ft³ (0.53 m³) Type of external material: Stainless Steel Type of internal material: Polystyrene Warranty: 3 / 5 years

Approvals ETL C&US;ETL SANITATION

N° of drawers: 2

Refrigeration Data

Compressor power: 1/10 hp
Operating temperature min.: 32 °F
Operating temperature max.: 41 °F
Condenser type: Fin & tube
Defrost type: Auto Defrost

Sustainability

Current consumption: 1.5 Amps
Refrigerant type: R600a
GWP Index: 3
Refrigerant weight: 70 g









