

**MODEL: IMD-ERC36B\_100\_130\_200  
 IMD-ERC130PH\_200PH\_PHBT**

**MERCHANDISER:  
 Glass Door Merchandiser ERC Series**



### GENERAL FEATURES

- ✓ **Higher energy efficiency.** R290 refrigerant with electric fans, LED lighting and evaporative tray without electric resistances.
- ✓ **Sanitation.** Our units feature a hygienic design with rounded corners that have a large radius, making them easy to clean. Additionally, the shelves and runners inside the display can be quickly removed for thorough interior cleaning. Each unit is equipped with a trap at the bottom to facilitate cleaning.
- ✓ **Doors.** Self-closing door system with permanent pressure. Stay open feature included when door remains open after 95 degrees. All doors include triple chamber door gaskets, easy to remove and snap in.
- ✓ **Control System.** Our temperature management system offers unparalleled precision, allowing for highly accurate temperature settings. With greater flexibility in adjusting temperature ranges, our system can be tailored to meet the unique needs of each end user. This ensures optimal performance and maximum satisfaction with every use.
- ✓ **Lighting.** LED lighting in the canopy and cabinet sides reduces the energy consumption by 80% to 90% compared to a traditional bulb, better light quality.
- ✓ **100% Tested.** All condenser units are 100% tested, in helium chambers for refrigerant leak detections.
- ✓ **Certified.** Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7.



Revision:02 Date: 05/03/2023 IMD-ERC\_PH\_PHBT

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE

**MODEL: IMD-ERC36B\_100\_130\_200  
 IMD-ERC130PH\_200PH\_PHBT**

**MERCHANDISER:  
 Glass Door Merchandiser ERC Series**

**STANDARD FEATURES**

➤ **Exterior**

- Back plastic-coated steel exterior.
- Completely injected compact structure.

➤ **Interior**

- Plastic coated steel interior.
- LED lighting, RGB.
- Internal drain.

➤ **Door**

- Pivot door (ERC130\_200PH/ ERC130\_200PHBT).
- Sliding doors with automatic closure system (ERC36B, ERC100, ERC130 y ERC200).
- Self-closing with stay open feature.
- Stainless Steel covered hinges.
- Triple chamber snap in door seals for easy removal.
- Door lock provided.
- Double pane glass door, tempered and low-e.

➤ **Insulation**

- CFC- Free polyurethane insulation, entire cabinet structure is foamed-in using a high-density polyurethane insulation.
- Low GWP & Zero ODP effect.

**OPTIONAL FEATURES**

- ✓ Black exterior / Black interior.
- ✓ White outside / White inside.

➤ **Shelving**

- Model IMD-ERC36B  
(4) inner shelves.  
Dimensions WxD: 21" x 13" (525x350mm).
- Models IMD-ERC100\_ERC130  
(4) inner shelf  
Dimensions WxD: 50" x 19" (1270x485mm).
- Models IMD-ERC130/PH/PHBT  
(4) white painted steel shelf.  
Dimensions WxD: 50" x 19" (1270x485mm).
- Models IMD-ERC200/PH/PHBT  
(8) white painted steel shelf  
Dimensions WxD: 38" x 19" (983x485mm).

➤ **Refrigeration**

- Temperature and defrost regulated by a digital controller.
- Evaporative pan.
- Evaporator coil coated with anti-corrosion material.
- Ventilated condensation system.
- **Refrigeration capacity:**  
 IMD-ERC36B – 2120 Btu/h(14°F)/621W(-10°C).  
 IMD-ERC100 – 3427 Btu/h(14°F)/1.004W(-10°C).  
 IMD-ERC130- 2881 Btu/h(14°F)/844W(-10°C).  
 IMD-ERC200 – 6858 Btu/h(14°F)/2.009W(-10°C).  
 IMD-ERC130PH – 6858 Btu/h(14°F)/2.009W(-10°C).  
 IMD-ERC200PH – 6858 Btu/h(14°F)/2.009W(-10°C).  
 IMD-ERC130PHBT- 4083 Btu/h(-22°F)/1.196 W(-30°C).  
 IMD-ERC200PHBT- 8166 Btu/h(-22°F)/2.392 W(-30°C).

➤ **Electrical**

- Cord and NEMA 5-15P plug,
- Electrical connection is 115V / 1ph / 60 Hz.



ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE





Project: \_\_\_\_\_  
Location: \_\_\_\_\_  
Item #: \_\_\_\_\_ Quantity: \_\_\_\_\_  
Model #: \_\_\_\_\_

**MODEL: IMD-ERC36B\_100\_130\_200  
IMD-ERC130PH\_200PH\_PHBT**

**MERCHANDISER:  
Glass Door Merchandiser ERC Series**

Revision:02 Date: 05/03/2023 IMD-ERC\_PH\_PHBT

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE



**INFRICO-North America Corporate División**  
1409NW 84<sup>th</sup> Avenue Doral FL 33126

[www.infrico.us](http://www.infrico.us)


**MODEL: IMD-ERC36B\_100\_130\_200  
 IMD-ERC130PH\_200PH\_PHBT**

**MERCHANDISER:  
 Glass Door Merchandiser ERC Series**


MODELS	Dimensions (inches) (mm)			Doors	Shelves	Ref	Ref. Weight (Lbs.) (gr.)	Temperature Range (°F) (°C)	Capacity (Cu.Ft.) (L)	Cond. Unit. H.P.	Case Amps 115V	Crated weight (Lbs.) (kg.)
	W	D	H									
ERC36B	24-3/8 (620)	25-5/8 (595)	73-3/8 (1.870)	1	4	R290	0,26 (120)	39°F/46°F (+4°C/+8°C)	10,59 (355)	1/3	4,78	154 (116)
ERC100	54-1/2 (1.385)	27-11/16 (704)	79 (2.005)	2	4	R290	0,31 (140)	39°F/46°F (+4°C/+8°C)	10,59 (1.110)	1/2	8,75	154 (284)
ERC130	54-1/2 (1.385)	31-11/16 (804)	79 (2.005)	2	4	R290	0,33 (150)	39°F/46°F (+4°C/+8°C)	10,59 (1.310)	3/4	6,19	154 (70)
ERC200	82 (2.081)	31-11/16 (804)	79 (2.005)	3	8	R290	0,33 (150)	39°F/46°F (+4°C/+8°C)	10,59 (1.890)	1	9,81	154 (70)
IMD-ERC130PH	54-1/2 (1.384)	33-1/8 (842)	78-7/8 (2.003)	2	4	R290	0,26 (120)	39°F/46°F (+4°C/+8°C)	40 (1.310)	3/4	9,88	386 (175)
IMD-ERC200PH	81-7/8 (2.081)	33-1/8 (842)	78-7/8 (2.003)	3	8	R290	0,33 (150)	39°F/46°F (+4°C/+8°C)	48 (2.100)	1	10,5	610 (277)
IMD-ERC130PHBT	54-1/2 (1.384)	33-1/8 (842)	78-7/8 (2.003)	2	4	R290	0,33 (150)	-0,4°F (-18°C)	40 (1.310)	1-1/4	11,37	386 (175)
IMD-ERC200PHBT	81-7/8 (2.081)	33-1/8 (842)	78-7/8 (2.003)	3	8	R290	0,33 (150)	-0,4°F (-18°C)	48 (2.100)	1-1/4	22,08	578 (262)

**PLAN VIEW**


**ELEVATION**



**PLANT VIEW**



**RIGHT VIEW**



**IMD-ERC36B**

Revision:02 Date: 05/03/2023 IMD-ERC\_PH\_PHBT

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE



**INFRICO-North America Corporate División**  
 1409NW 84<sup>th</sup> Avenue, Doral FL 33126  
 (305) 777 9599 ext.700 / f (305) 777 9598  
 Toll Free 855-340-4637

[www.infrico.us](http://www.infrico.us)  
[sales@infrico.com](mailto:sales@infrico.com)




**MODEL: IMD-ERC36B\_100\_130\_200**  
**IMD-ERC130PH\_200PH\_PHBT**

**MERCHANDISER:**  
**Glass Door Merchandiser ERC Series**




**ELEVATION**

**PLANT VIEW**

**RIGHT VIEW**



**ERC130**






**ERC200**




ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE

**MODEL:IMD-ERC36B\_100\_130\_200  
 IMD-ERC130PH\_200PH\_PHBT**

**MERCHANDISER:  
 Glass Door Merchandiser ERC Series**



**IMD-ERC130PH  
 IMD-ERC130PHBT**



**IMD-ERC200PH  
 IMD-ERC200PHBT**

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE