

UNIVERSAL ANGLE UTILITY RACK MODEL 207-UA-13A

FEATURES AND BENEFITS:

- Durable utility rack for transport and storage of products on a large variety of pan sizes.
- Fully welded framework of structural aluminum extrusions for rigidity and durability.
- Constructed of non-corrosive, Hi-Tensile aluminum for strength.
- Chrome plated wire universal angles adjustable on 1-1/2" centers. Thirteen sets of angles provided, twelve are adjustable.
- Heavy duty 5" swivel casters, two with brakes. Provides mobility when fully loaded.



207-UA-13A
(Pans not included)




ACCESSORIES and OPTIONS (Available at extra cost):

- Extra Universal Angles
- Pan Stop
- Corner Bumpers
- Vertical Bumpers
- Perimeter Bumper

See page G-36 for accessory details.



207-UA-13A



CRES COR MODEL NO.	PAN			DIM "A"	DIM "B"	DIM "C"	INSIDE DIMENSIONS				WEIGHT ACT.
	CAP/ ANGLES	SIZE		WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT		
207-UA-13A	13 SETS	SEE NOTE BELOW	IN	25-3/8	24-15/16	69-3/4	21-3/4	24-3/8	61-1/2	LBS	68
			MM	645	635	1775	555	620	1565	KG	31

NOTES: 1. Pan sizes 22" x 20" (560 x 510) Roast & Bake Pans, 10" x 20" (255 x 510) Roast & Bake Pans, 18" x 26" (460 x 660) Bun Pans, 14" x 18" (355 x 460) Service Trays, 12" x 20" (305 x 510) Steam Table Pans. Refer to Pan Size Chart at end of section.
 2. When ordering bumpers, add 2" to overall dimensions.

ALL ALUMINUM CONSTRUCTION IS WELDED AND FINISHED.



Gold indicates our Best Rack with the best warranty in the industry. 3-Year Parts / 1-Year Labor with lifetime guarantee against rust & corrosion

RACK:

- Posts: Extruded channels, 1-1/16 x 2 x .125.
- Top and bottom: Extruded channels, 1-1/16 x 2-3/8 x .188; welded to posts.
- Tie rods (2): 5/16 dia. steel rods enclosed in aluminum tubing; fastened to posts.
- Casters: 5" dia., swivel, modulus tires, 1-1/4 wide, load cap. 250 lbs. each, temp. range -4°/+140°F. Delrin bearings. Two casters equipped with brakes.

PAN SLIDES:

- Wire angles (.306 dia.), nickel chrome plated steel, spaced on 4-1/2" centers, adjustable on 1-1/2" centers.
- Bottom extruded angle, welded to posts.

SHORT FORM SPECIFICATIONS

Cres Cor Utility Rack Model 207-UA-13A. Extruded aluminum welded construction. Tie rods (2) applied at front and rear. (13) sets wire universal angles for multiple pan sizes, adjustable spacing every 1-1/2". 5" swivel modulus casters, Delrin bearings. Load capacity 250 lbs. each, temperature -4° to +140°F. 3-Year Parts / 1-Year Labor warranty. Lifetime guarantee against rust & corrosion. Provide the following accessories: _____ . NSF listed.