



POWER PACK - WATER COOLED

PREMIUM - 2 PUMP - 2,300 BTUs

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Anti-vibration pads reduce motor noise.
- Exterior sight glass to verify glycol bath level.
- Rugged stainless steel cabinet.




Reverse side showing water connections.



MMPP4301-PKG-WC

Water Cooled:

Designed for spaces with limited air circulation or high ambient temperature.



L5-30P



Part No.	Description	Shipping Weight
MMPP4301-PKG-WC	Water cooled power pack, 2 pump and motor	58 kg
		128 lbs

Operating Performance

Compressor	1/3 HP	Pump Type	Rotary Vane
BTU per hour	2,300	Push In Connector	12.7mm (1/2") O.D.
Plug Type (NEMA #)	L5-30P	Water Inlet & Outlet Fitting	Female 3/8" NPT
Voltage	115	Minimum Water Pipe Size	3/8"
Running	17.2A	Inlet Water Pressure	Minimum 40 psi / Maximum 120 psi
Refrigerant	R-134a	Water Usage	.3 GPM. Water is only used when the temperature of the condenser rises high enough to open the cooling inlet valve. This is approximately 40% of the operating time depending on ambient temperature and usage.
Charge	0.34 kg (12 oz)		
Refrigerant Running Pressure	18 (low) 140 (high)		
Bath Capacity	43.5 litre (11.5 gallons)		
Condenser Inlet Water Temperature	Minimum 45° F / Maximum 80° F		

Dimensions

