

Dis-assembling | CLEANING | Re-assembling

For more detailed information on operation and cleaning, go to www.citrusamerica.com/training



1. Empty fruit basket and fruit supply tunnel. Remove **fruit basket** by gently turning it to the right.



2. Remove **rotation plate**.



3. Clean **basket area** with soft damp towel. Dry. **DO NOT CLEAN UNDER RUNNING WATER. DO NOT TAKE OFF.**



4. Remove **splash protector**.




5. Remove **side chutes** by pressing the fastening clips and sliding chutes upward out.

HANDWASH ONLY!




6. Remove **front cover**: pull lower part out and lift away from retaining bolts up top.


HANDWASH ONLY!



7. Loosen cross holder screw and remove **cross holder** and screw as one unit.




8. Pull out **cross holder screw** → 3 parts: cross holder, screw, knife guide.




9. Remove **peel ejectors**.



10. Remove **upper pressing elements**.




11. Remove **lower pressing elements**.



12. Lift **knife** and pull it out. **CAUTION: BLADE IS RAZOR SHARP!**



13. Open **supply tunnel** locking lever and remove supply tunnel.




14. Remove **double cover** (back plate).




15. Unscrew **SB tap** from machine.





16. Unscrew and separate the upper tap from lower tap. Rinse both parts.




17. Remove **ATS system** by lifting front edge slightly and pulling it toward you. **HANDWASH ONLY!**



24. **Re-installing the ATS System:** Ensure that the **drive shaft** of the ATS belt (1) fits correctly into the **drive shaft adapter** (2). Use the **adjustment screw** (3) to install the ATS belt correctly.



19. Unscrew fruit sieve nut and remove **sieve support**.



20. Take off all **removable parts on cabinet:** peel chutes, grate, peel funnel, drip tray and plate.

1. **BEFORE CLEANING SWITCH OFF AND UNPLUG JUICER.**
2. **CLEAN JUICER AT LEAST 1X DAY!**
3. **ENSURE THAT ALL PARTS ARE MOUNTED PROPERLY AFTER REASSEMBLY**
4. **IF YOUR JUICER DOES NOT START AFTER INPUT FROM ON/OFF SWITCH, REFER TO THE CONTROL PANEL.**
5. **KEEP THESE INSTRUCTIONS NEAR JUICER!**



ALL PARTS EXCEPT FOR THE PLASTIC FRONT COVER, SIDE CHUTES, AND JUICE TANK ARE DISHWASHER SAFE.

TECH SUPPORT:



FRONT COVER, SIDE CHUTES, AND JUICE TANK ARE HANDWASH ONLY. USE A NON-ABRASIVE DETERGENT AND A SOFT TOWEL FOR CLEANING.

1-855-MY-CITRO

(1-855-692-4876)

DO NOT SPRAY OR HOSE DOWN THE MACHINE. ONLY WIPE DOWN.