



# BEVERAGE-AIR

|                 |      |
|-----------------|------|
| Project: _____  | AIA# |
| Item: _____     |      |
| Location: _____ | SIS# |
| Approved: _____ |      |

**WTR67AHC SIDE MOUNT WORKTOP REFRIGERATOR**

## SIDE MOUNT WORKTOP WTR67AHC Solid Door Refrigerator Hydrocarbon Series

**MODEL:  
WTR67AHC**



**7 Year Parts/Labor Warranty  
7 Year Compressor Warranty**

### CABINET CONSTRUCTION

- Stainless steel front, sides, doors and grille (galvanized back & bottom)
- Interior liner is made of corrosion resistant aluminum
- Stainless steel top for added durability
- 16 Gauge stainless steel top
- Full electronic control
- Interior thermometer is standard
- 4" Foamed-in-place backsplash
- Self-closing doors with 120° stay-open feature
- Easy door removal for service and cleaning
- Magnetic gaskets attached to each door for positive seal
- 6" Casters, two (2) with brakes standard
- Four (4) epoxy-coated steel wire shelves
- Field-reversible doors

### OPTIONS & ACCESSORIES

- Stainless steel back
- Stainless steel interior
- Additional shelves
- Shelf clips
- Right or left hinged door
- Door locks
- Wire shelf divider
- 3" Casters
- 6" Legs (stainless steel, black or seismic/flange)
- Low profile casters
- Roller kit
- Flat-top with no backsplash (-FLT)
- Remote option\* (see note on back on page)

### REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Adaptive defrost
- Epoxy coated evaporator coil
- Refrigerators capable of maintaining product temperature between 36°F and 38°F



  
Please verify qualifying units by visiting:  
[www.energystar.gov/cfs](http://www.energystar.gov/cfs)

3779 Champion Blvd., Winston-Salem, NC 27105  
1-888-845-9800 Fax: 1-336-245-6453  
Beverage-Air.com Sales@bevair.com



# BEVERAGE-AIR

| MODEL                              | WTR67AHC          |
|------------------------------------|-------------------|
| <b>EXTERNAL DIMENSIONAL DATA</b>   |                   |
| Width Overall                      | 67"               |
| Depth Overall with Handle & Bumper | 35 3/4"           |
| Height Overall with 6" Casters     | 39 1/2"           |
| Number of Doors                    | 2                 |
| Depth with Door Open 90°           | 57 1/8"           |
| Door Openings                      | 21 5/8" x 23 5/8" |
| <b>INTERNAL DIMENSIONAL DATA</b>   |                   |
| NET Capacity (cubic ft.)           | 18.97             |
| Internal Width Overall (in)        | 63"               |
| Internal Depth Overall (in)        | 26"               |
| Internal Height Overall (in)       | 25"               |
| Number of Shelves                  | 4                 |
| <b>ELECTRICAL DATA</b>             |                   |
| Full Load Amperes                  | 2.0               |
| Voltage                            | 115/60/1          |
| Nema Plug (8' cord)                | 5-15P             |
| <b>REFRIGERATION DATA</b>          |                   |
| Horsepower                         | 1/5               |
| Capacity (BTU/Hr)                  | 1350              |
| Heat Rejection (BTU/Hr)            | 2025              |
| Charge (lbs/grams/ounces)          | 0.243 / 110 / 3.9 |
| <b>SHIPPING DATA</b>               |                   |
| Gross Weight - Crated              | 400 lbs           |
| Height - Crated                    | 44"               |
| Width - Crated                     | 69"               |
| Depth - Crated                     | 35"               |

\*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).

## Worktop Refrigerator - Side Mount Model: WTR67AHC

**Model Views**

Required Clearance: 3" Bottom & 2" Rear

**PLAN VIEW**

**ELEVATION VIEW**

**SIDE VIEW**



### ELECTRICAL CONNECTION



115/60/1  
NEMA 5-15P

Unit pre-wired at factory and include 8' long cord and plug set.