

Project:	AIA#
Item:	
Location:	SIS#
Approved:	

BAR EQUIPMENT- BACK BAR REFRIGERATOR

BB72HC Sliding Glass Door Hydrocarbon Series

MODEL: BB72HC-1-GS-B



7 Year Parts/Labor Warranty 7 Year Compressor Warranty

CABINET CONSTRUCTION

- Exterior features durable black painted steel
- Interior construction utilizes galvanized steel on walls and ceiling, heavy duty stainless steel floor
- Full electronic control
- Galvanized sub-top standard
- Self-closing sliding glass doors have black frame regardless of
- Stay-open feature and locks standard
- Magnetic door gaskets provide positive door sealing
- LED lighting
- Packaged products only
- Six (6) epoxy coated wire shelves
- · Compressor available on left or right, specify at time of unit order
- Balanced, forced air refrigeration system provides rapid chilling of product

OPTIONS & ACCESSORIES

- For stainless steel interior (refer to -F models)
- 2" Stainless steel top
- Wine model (40°-60° models)
- · Wire shelf divider
- Additional shelves
- · Additional shelf clips
- 3" or 6" Casters
- 6" Black legs
- Remote option* (see note on back on page)

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Adaptive defrost
- · Epoxy coated evaporator coil
- Maintains product temperature between 36°F and 38°F










MODEL	BB72HC-1-GS-B	
EXTERNAL DIMENSIONAL DATA		
Width Overall	72"	
Depth Overall	23 %"	
Height Overall	34"	
Number of Doors	3	
Door Opening (in)	18 ½" x 26 ¼"	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	19.92	
Internal Width Useable (in)	60 ¼"	
Internal Depth Overall (in)	18 ½"	
Internal Height Overall (in)	29 %"	
Number of Shelves	6	
Number of 1/2 Kegs	3	
ELECTRICAL DATA		
Full Load Amperes	3.1	
REFRIGERATION DATA		
Horsepower	1/3	
Capacity (BTU/Hr)	1942	
Heat Rejection (BTU/hr)	2913	
Charge (lbs/grams/ounces)	0.3086 / 140 / 4.9	
SHIPPING DATA		
Gross Weight - Crated	381 lbs	
Height - Crated	43"	
Width - Crated	75"	
Depth - Crated	27"	

*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4*. Metric dimensions (MM).

Bar Equipment-Back Bar Refrigerator Model: BB72HC-1-GS-B







ELECTRICAL CONNECTION

115/60/1 NEMA 5-15P Unit pre-wired at factory and include 8' long cord and plug set.

