



## **CERTIFIED INSTALLATION PROGRAM and PRE-INSTALL CHECKLIST**

The Angelo Po authorized service agent will arrange for proper installation of your Angelo Po equipment. Any additional costs beyond those provided as part of the Angelo Po Certified Installation Program are the responsibility of the customer.

### Angelo Po Certified Installation Program includes the following:

1. Travel by Angelo Po America Inc. or its designee, within (50) mile radius (one hundred miles round trip) of Angelo Po America Inc. or its designee's office.
2. Assembly, setting, and leveling of the Angelo Po equipment
3. Drain lines, drain vent pipes, and gas connections when Certified Installation performed as part of CombiCare package
4. Start-up demonstration
5. Three (3) year warranty from date of installation or thirty-nine (39) months from the shipping date, whichever occurs first. This is a (1) one year increase over the standard two (2) year warranty.

The **PRE-INSTALLATION CHECKLIST** must be completed before install can begin. This checklist can be found at the end of this document. Contact Angelo Po offices to schedule install. Scheduling of installation can begin upon confirmation that the oven has arrived at the install location. Please allow up to 2 weeks between contacting Angelo Po and completion of certified install by an authorized service agent.

On the scheduled day of installation, the customer must ensure that the Angelo Po equipment is properly positioned within six (6) feet of the installation location and that the work area (within six feet of the equipment) is free and accessible for the Angelo Po authorized service agent to work.

If the installation of the Angelo Po equipment cannot be completed due to local codes and/or government authorities, or if there is a disruption in electrical, gas or water service at the time of installation, or if the Angelo Po authorized service agent is unable to access the utilities due to activities at the facility beyond his/her control, the Angelo Po authorized service agent will, upon request, complete the final installation at a later date to be determined by Angelo Po America Inc. The use of any additional contractor labor, travel and/or parts other than those specified in the Angelo Po Certified Installation Program, is the responsibility of the customer.



The Angelo Po Certified Installation Program does **not** include the following:

1. Overtime travel or labor
2. Installation of the Angelo Po equipment beyond (50) mile radius (one hundred miles round trip) of Angelo Po America Inc. or its designee's office will require an additional travel charge.
3. Any work or costs associated with moving the equipment within six (6) feet of the final installed location
4. Special licensing or permits
5. Unpacking, uncrating, and removal of packing material of Angelo Po equipment
6. Removal and scrapping of old equipment
7. Installation of water filtration systems other than the APA RO system. Copper supply lines with shutoff valves, additional tubing, fittings, or any additional water supplies are the end-user's responsibility.
8. Electrical connections such as power cords, cord restraints plugs, and receptacles other than those provided with the equipment.

**SPECIAL NOTICE:**

Any installation of the above items not included in the Angelo Po Certified Installation is the responsibility of the end-user customer.

Installation of the Angelo Po oven's hose reel or spray hose is to be performed by the Angelo Po Authorized service agency only.

Installation of the Angelo Po oven onto an Angelo Po stand is to be performed by the Angelo Po Authorized service agency only.

Installation of Angelo Po ovens on to any counter or other manufacturers equipment is to be performed by the end-users installer and is the full responsibility of the end-user to ensure the oven placement is secure and safe.

**Dealer/Designer/Consultant Responsibilities:**

Full completion and submission of the Pre-Installation Checklist to Angelo Po America. Installation cannot begin until this document is received and approved by the Angelo Po technical team.

Dealer Responsibilities include: Inspect, receive, deliver, un-crate, and set oven in place. Check that all accessories are unpackaged and set up for the end user. Verify electric ovens match voltage supply with ovens specific voltage prior to placing order.

**Plumbing Requirements:**

Provide (3/4" NPT) gas supply line with shut off valve connections verifying proper type, and pressure to the unit. Provide water connections to 3/4" cold water lines with required 30-60 psi. Complete oven drainpipe 1 1/4" runs from bottom of oven to floor drain. Provide vent stack from top of drain tee to extend 4" above top of oven. 3 Gas Supply.

All gas supply hoses and connections must be available at time of installation. The end user must install gas shut off ball valve. Service technician will install customer's gas hose to the ball valve and make the final connections to oven and make final gas connections and installation.

**Electrical Requirements:**

Install proper electrical voltage, phase, wire size, and breaker size for final connections to be made. Oven cannot be connected to G.F.I. receptacle.



# DEALER PRE-INSTALLATION CHECK LIST

PURCHASE ORDER #: \_\_\_\_\_ DATE: \_\_\_\_\_

ON SITE CONTACT: \_\_\_\_\_ SITE CONTACT PHONE #: \_\_\_\_\_

END USER BUSINESS NAME: \_\_\_\_\_

USER EMAIL: \_\_\_\_\_ STREET ADDRESS: \_\_\_\_\_

END USER PHONE #: \_\_\_\_\_ CITY / STATE / ZIP: \_\_\_\_\_

BY SIGNING BELOW, THE END USER CERTIFIES THAT THEY HAVE READ THE ABOVE CERTIFIED INSTALL PROGRAM IN ITS ENTIRETY AND ARE AWARE OF THEIR RESPONSIBILITIES IN THIS REGARD. ANY ADDITIONAL EXPENSES INCURRED WILL BE THE RESPONSIBILITY OF THE END USER AND NOT COVERED BY ANGELO PO AMERICA OR THEIR AUTHORIZED SERVICE AGENT.

END USER NAME (PRINT): \_\_\_\_\_ END USER NAME (SIGN): \_\_\_\_\_

### 1. Type of Premises:

New Restaurant \_\_\_\_\_ Existing Restaurant \_\_\_\_\_ Hotel \_\_\_\_\_ Hospital \_\_\_\_\_

School / University \_\_\_\_\_ Production Kitchen \_\_\_\_\_ Other \_\_\_\_\_

### 2. Indicate model below and provide installation and ingress conditions

Indicate Model	Model Number	Width	Depth including handle & rear drain	Height including feet and flue
	FX61	36.3	34	30.8
	FX101	36.3	34	40.5
	FX82	46.4	41.4	36.7
	FX122	46.4	41.4	47
	FX201	36.6	34.6	72.6
	FX202	46.6	41.6	72.6
	FX82 Double Stack	48.3	46	74.4
	FX82 Double Stack on Caster Frame	48.3	46	78.4

- a. Are the door dimensions suitable? Yes \_\_\_\_\_ No \_\_\_\_\_
- b. Are the corridor dimensions suitable for all ovens? Yes \_\_\_\_\_ No \_\_\_\_\_
- c. Are the lift dimensions and capacity suitable? Yes \_\_\_\_\_ No \_\_\_\_\_
- d. Floor slope allows the appliance to be leveled correctly. Yes \_\_\_\_\_ No \_\_\_\_\_

**3. Type of installation**

Open base frame \_\_\_\_\_ Closed base cabinet \_\_\_\_\_ Tabletop \_\_\_\_\_  
 Floor installation \_\_\_\_\_ On top of blast-chiller \_\_\_\_\_ Double Stack \_\_\_\_\_  
 Distance from adjacent walls, floor and hood in inches  
 Right \_\_\_\_\_ Left \_\_\_\_\_ Rear \_\_\_\_\_ Lower \_\_\_\_\_ Upper \_\_\_\_\_

**Adjacent appliances.**

1. Right Side: Type \_\_\_\_\_ Distance \_\_\_\_\_
2. Left Side: Type \_\_\_\_\_ Distance \_\_\_\_\_

**Ventilation system Hood Type:**

- Is there a ventilation hood system? Yes \_\_\_\_\_ No \_\_\_\_\_
- a. Hood Type \_\_\_\_\_
  - b. Exhaust hood with makeup air built in \_\_\_\_\_
  - c. Exhaust hood without makeup air \_\_\_\_\_

**4. Water Connection**

- \* Are there two water lines within 36 inches of the oven with 3/4 shut off valves? Yes \_\_\_\_\_ No \_\_\_\_\_
- \* Is the water pressure between 30 psi – 60 psi without Reverse Osmosis? Yes \_\_\_\_\_ No \_\_\_\_\_
- \* Indicate distance of water connections to oven (in inches) \_\_\_\_\_

- ❖ Minimum 60 psi Reverse Osmosis water treatment system is installed
- ❖ When an oven is installed without an Angelo Po supplied water treatment system a water test must be submitted. Remember to write Angelo Po on the water test paperwork

Has a water test been submitted? Yes \_\_\_\_\_ No \_\_\_\_\_

**5. Water Drain / Vent Riser**

Is there a working drain within 5 feet of the oven that can ensure minimum 5% slope? Yes \_\_\_\_\_ No \_\_\_\_\_  
 Diameter of drain \_\_\_\_\_ Length from oven to drain: \_\_\_\_\_

- ❖ CombiCare ovens sales include CPVC drain materials for up to 8 feet from oven.
- ❖ All other sales the materials are the responsibly of the end user.

**6. Electrical connection: NOTE: OVENS MUST NOT BE CONNECTED TO A GFCI OUTLET.**

Breaker Size Amp \_\_\_\_\_ Verified Voltage \_\_\_\_\_

Is there an electrical connection within 5 feet of the oven that matches the electric requirements below? Yes \_\_\_\_\_ No \_\_\_\_\_

Model	Voltage	Amperage	Model	Voltage	Amperage
FX61E3	208	26.1	FX122E3	208	72.3
FX61E3	240	25	FX122E3	240	62.6
FX61E3	480 Not Available in US		FX122E3	480	31.3
FX101E3T	208	49.3	FX201E3	208	98.7
FX101E3T	240	43.1	FX201E3	240	86.2
FX101E3T	480	21.6	FX201E3	480	43.1
FX82E3T	208	57.5	FX202E3	208	144.5
FX82E3T	240	49.9	FX202E3	240 Not Available in US	
FX82E3T	480	24.9	FX202E3	480	62.6
GAS OVENS			GAS OVENS		
Model	Voltage	Amperage	Model	Voltage	Amperage
FX61G3	120	4.8	FX122G3	120	11.5
FX101G3	120	6.9	FX201G3	120	15.1
FX82G3	120	7.8	FX202G3	120	22

**7. Gas connection:**

- a. Gas Type: Natural: \_\_\_\_\_ Propane: \_\_\_\_\_
  - b. **The appliance requires an appropriate 3/4" NPT connection with shut off valve**
  - c. Gas connection is within 3 feet of oven: Yes \_\_\_\_\_ No \_\_\_\_\_
  - d. Is there a gas shut-off valve installed for each oven: Yes \_\_\_\_\_ No \_\_\_\_\_
- ❖ **Ovens sold as CombiCare will have a gas hose supplied**
  - ❖ **Standard oven sales remain the responsibility of the end user to have on site for installation.**
  - ❖ **A separate gas hose is required for each oven being installed.**

**8. Special requirements for models FX201-FX202:**

- a. Is the floor slope more than 2% to a floor drain or floor level? Yes \_\_\_\_\_ No \_\_\_\_\_
- b. Is there adequate maneuvering space for the cart? Yes \_\_\_\_\_ No \_\_\_\_\_
- c. Are there floor grilles or discharge outlets in the cart maneuvering area? Yes \_\_\_\_\_ No \_\_\_\_\_

**9. Travel & Mileage allowance:**

- ❖ Should installation location exceed 2-hours travel time and/or 100 miles' round trip from closest authorized service agency, end user will be responsible for additional travel charges beyond the 2-hour/100 mile' allowance.

**10. This Service Agreement allows our Authorized Service Agents 2 visits. One to do a site inspection prior to install and one to perform the final installation. Any additional visits will incur charges that are not the responsibility of Angelo Po America and will be billed to the end user directly.**

**All utilities must be fully operational at the time of install.**

Notes:

---



---



---



---

Accurate completion of the Pre-Install Checklist ensures a smooth installation process. Returns of equipment will not be accepted due to inaccuracies or misrepresentations in the completing of this form.

Survey conducted by:

Name (PRINT): \_\_\_\_\_ Name (SIGN): \_\_\_\_\_

Representing: \_\_\_\_\_

Requested date of install: \_\_\_\_\_ Date checklist completed: \_\_\_\_\_

- ❖ Service agencies will require a Minimum of 1½ week advance notice for scheduling once a delivery date has been set.
- ❖ Installation to be completed during normal business hours, (8:00am to 5:00pm M-F)
- ❖ Additional trip charges are the responsibility of the end user when site is not ready on scheduled date of installation as confirmed with Customer, General Contractor or Sales Representative.

Angelo Po Technical Service approval: \_\_\_\_\_ Date: \_\_\_\_\_

SIGN WHERE REQUESTED AND RETURN ALL 6 PAGES TO THE MANUFACTURER