CN48-20V SERIES **RESTAURANT GAS RANGE**







STANDARD FEATURES:

ACCESSORIES

- Stainless 1" thick Steel, front, sides, riser, lift-offhigh
 Casters (set of four) shelf
- 6" stainless steel adjustable legs
- 8 open top burners of 34,000 Btu's each
- · Energy saving flash tube pilot systems (i.e. one pilot per two burners)
- Heavy Duty cast iron grates
- Full depth, pull out crumb tray
- Bake n' Roast oven @ 35,000 Btu's; fits full sized sheet pans
- One oven rack with three positions




- Extra oven rack
- 12" stainless steel stub back



OPTIONS

• 24" - 48" wide x 1" thick griddle





INSTALLATION INSTRUCTIONS

- **01.** A pressure regulator sized for this unit is included. Natural gas 5.0" W.C., propane gas 10.0" W.C.
- **02.** Gas line connecting to range must be 3/4" or larger. If flexible connectors are used, the inside diameter must be 3/4" or larger.
- O3. An adequate ventilation system is required for Commercial cooking equipment. Information may be obtained by writing to the National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02269, www.NFPA.org. When writing, refer to NFPA No. 96
- **04.** These units are manufactured for installation in accordance ANSZ223.1A (latest edition), National Fuel Gas Code. Copies may be obtained from American Gas Association, 400 N Capital St. NW, Washington, DC 20001, www.AGA.org.

05.	Clearances Combustible	Rear 6"	Sides 10"
	Standard Oven Non-combustible	O"	O"
	Convection Oven Non-combustible	Min. 4"	0"

06. For proper combustion, install equipment on adjustable legs or casters provided with unit.

SPECIFY TYPE OF GAS WHEN ORDERING SPECIFY ALTITUDE WHEN ABOVE 2,000 FEET



Connerton reserves the right, without notice, to make changes and revisions in product specifications, materials and design, which in our opinion will provide better performance, durability and efficiency.