

| Project: | AIA# |
|-----------|------|
| ltem: | |
| Location: | SIS# |
| Approved: | |

HORIZON TOP MOUNT REACH-IN

HFS3HC Half-Solid Triple Door Reach-In Freezer

Hydrocarbon Series





7 Year Parts/Labor Warranty 7 Year Compressor Warranty

CABINET CONSTRUCTION

- Exterior is stainless steel front and continuous coil coated sides
- Stainless steel interior
- Full electronic control
- Expansion valve technology
- One piece grille
- LED interior light
- Self-closing door with 120° stay-open feature, on cam-lift hinges
- Field reversible doors
- Door locks
- Snap-in magnetic gaskets for positive door seal
- Nine (9) heavy-duty epoxy coated wire shelves
- 6" Heavy-duty casters, two (2) with brakes
- 8' Cord and plug (see electrical data for details)

OPTIONS & ACCESSORIES

- Tray slide pair, 1 tray slide set for (1) 18" x 26" or (2) 14" x 18" pans (A)
- Stainless steel universal tray slide pair,1 tray slide set for (1) 18" x 26" or (2) 14" x 18" pans (AC)
- Tray slide kit #4 (19 sets per half section)
- Additional epoxy shelves
- · Shelf clips
- · Stainless steel breaker
- 6" Legs seismic/flanged
- 3" Casters
- Remote option* (see note on back page)

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE &
- Hot gas condensate evaporator
- · Adaptive defrost
- Epoxy coated evaporator coil
- Freezer capable of maintaining product temperature down to -10°F












| MODEL | HFS3HC-1HS | |
|------------------------------|---------------------|--|
| EXTERNAL DIMENSIONAL DATA | | |
| Width Overall | 78" | |
| Depth Overall with Handle | 33 %" | |
| Height Overall | 85" | |
| Number of Doors | 6 | |
| Depth with Door Open 90° | 55 ½" | |
| Door Opening (in) | 21 %" x 29 %" | |
| INTERNAL DIMENSIONAL DATA | | |
| NET Capacity (cubic ft.) | 69.1 | |
| Internal Width Overall (in) | 74" | |
| Internal Depth Overall (in) | 25 %" | |
| Internal Height Overall (in) | 62" | |
| Number. of Shelves | 9 | |
| ELECTRICAL DATA | | |
| Full Load Amperes | 13.2 | |
| Voltage | 115/60/1 | |
| Nema Plug (8' cord) | 5-15P | |
| REFRIGERATION DATA | | |
| Horsepower | (2) 3/4 | |
| Capacity (BTU/Hr) | 3854 | |
| Heat Rejection (BTU/Hr) | 5781 | |
| Charge (lbs/grams/ounces) | 0.2866 / 130 / 4.59 | |
| SHIPPING DATA | | |
| Gross Weight - Crated | 744 lbs | |
| Height - Crated | 88" | |
| Width - Crated | 81" | |
| Depth - Crated | 36" | |

*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).

Top Mount Reach-In Freezer Model: HFS3HC-1HS





ELECTRICAL CONNECTION



Unit pre-wired at factory and include 8' long cord and plug set.

