

Project:	
Model #:	
Item #:	
Available W/H:	Qty:
Approval:	
AIA #:	SIS #:
CSI Section 11400	

Top Open Island Freezer

Model : TFS-25F-N



≡ FEATURES & BENEFITS ≡

- **Hydrocarbon refrigerants (R-290)**
 With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).
- **High-density polyurethane insulation**
 The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- **Horizontal display freezer for high impulse sales**
 Flat lid display freezer provides convenient access and fast service and is ideal for high impulse sales such as frozen treats. Minimal frame glass lids allow excellent visibility with maximum merchandising effect.
- **Tempered, energy-saving, Low-E glass sliding top**
 Energy saving Low-emissivity glass top reduces outer heat gain and lowers energy consumption. Reinforced tempered glass lids for safety.
- **White, anti-rust coating on the exterior reduces fingerprints**
- **LED interior lighting with on/off switch**
- **External digital temperature control**
- **Painted white powder-coated steel interior**
- **Two layers of rubber bumper guards around the cabinet**
- **Manual defrost system with drain**
- **Wire baskets come standard**
- **Freezer holds -10°F ~ 8°F for the best in frozen food preservation**


NATURAL Refrigerant



Model	Sliding Doors	CU./FT.	#of Baskets	HP	AMPS	Crated Weight (lbs.)	L x D x H* (inches)
TFS-25F-N	2	25.22	33	1/2	4.6	520	69 x 31 1/2 x 31 1/4

Top Open Island Freezer

Model : TFS-25F-N

ELECTRICAL DATA	
Voltage	115/60/1
Plug Type	 NEMA 5-15P
Full Load Amperes	4.6
Compressor HP	1/2
Cord Length (ft.)	7
Refrigerant	R-290
DIMENSIONAL DATA	
# of Sliding Doors	2
Net Capacity (cu. ft.)	25.22
Net Capacity (Gal.)	188.7
Ext. Length Overall (in.)	69 (1750mm)
Ext. Depth Overall (in.)	31 1/2 (800mm)
Ext. Height Overall (in.)*	31 1/4 (793mm)
Int. Length Overall (in.)	63 5/8 (1614mm)
Int. Depth Overall (in.)	26 1/8 (664mm)
Int. Height Overall (in.)	23 7/8 (607mm)
# of Baskets	33
Basket Size (L x D x H) (in.)	(3) 10 3/8 x 8 x 8 3/4
	(30) 9 5/8 x 8 x 9 1/2
Net Weight (lbs.)	470
Gross Weight (lbs.)	520

Design and specifications subject to change without notice.
Actual shipping weight may differ due to extra packing materials for product protection.
* Height does not include 3" for caster height.

■ **WARRANTY : 2 Year Parts and Labor Warranty**
Additional 3 Year Warranty on Compressor

■ **STANDARD FEATURES**


- No plumbing required
- Self-contained system
- 2.5 dia. casters, two locking

■ **Recommended operating conditions**


TFS models are designed to operate in air conditioned environments where temperature and humidity are below 75°F and 55% relative humidity. Place units away from direct sunlight, rapid air movement and extreme temperature changes

PLAN VIEW


(unit : inch)



TOP VIEW



FRONT VIEW



SIDE VIEW

Ver.20230802

NATURAL Refrigerant



- Turbo Air : 800-627-0032
- GK : 800-500-3519
- Warranty : 800-381-7770
- AC : 888-900-1002

Turbo air REFRIGERATOR MANUFACTURER

GERMAN KNIFE

RADIANCE

Turbo air REFRIGERATION SYSTEM

TEXAKING

Continued product development may necessitate specification changes without notice.