



Item No. _____
Project _____
Quantity _____

Electric, Cruiseline Griddle

Model: CLG[24,36,48,60,72]



Model CLG36 shown

SIZING AND PERFORMANCE GUIDE

Table with 4 columns: Model/Width, Surface Area, Controls, kW Input*. Rows include CLG24, CLG36, CLG48, CLG60, and CLG72.

* 6-kW per foot of griddle

** Total power input, two power connections required

CRUISELINE SHORT/BID SPECIFICATION

Griddle shall be a LANG Manufacturing Cruiseline Specification Model CLG-__ [Specify width: 24", 36", 48", 60" or 72"], with: all heavy gauge 304 stainless steel construction...

CRUISELINE PRODUCT WARRANTY

- One year, parts & labor (Labor in U.S. Port only)
• 5-year warranty against rust-through (Exceeds USPH requirements)

CRUISELINE CONSTRUCTION FEATURES

- All Type 304 stainless steel construction
• Seams are continuously welded, ground and polished
• USPH fasteners used throughout
• 1" thick precision machined, polished steel plate
• Continuously bottom welded 5-1/2" high rear splash
• Full front 3-1/2" wide X 1" deep stainless steel trough
• 8 quart capacity grease drawer, with marine latch, enclosed sleeve [Two on 60" & 72" models]
• Fully enclosed air cooled control compartments
• Full width front mounted grab bar
• 4" adjustable bolt-down legs provided [USPH]

PERFORMANCE FEATURES

- All welded seams for easy cleaning
• All Type 304 stainless steel construction
• Thick griddle plate reduces hot & cold spots
• Highly polished surface and continuously welded trough speed cleanup
• Heating elements Incoloy sheathed, for long life
• Elements are pressure clamped to bottom of even heating
• Recessed control panel protects control knob
• Accurate temperature control between 175° and 450°F

CONTROL PACKAGE

- Snap-action thermostats
• Independent temperature control every 12"
• Power-to-element pilot lights for each control



Sheet No. LCLS-1 (rev. 06/17)



Electric, Cruiseline Griddle


Model: CLG[24,36,48,60,72]

CRUISELINE INSTALLATION REQUIREMENTS


- **E** 440V, 3-phase, 60 Hz power connection
- **E** **E2** Two power connections required for 60 & for 72" wide units
- Installation under approved vent hood required.
[Connections from rear. See other below for location and power requirements]

CRUISELINE OPTIONS & ACCESSORIES


- Other Voltages [Consult Factory]
- Custom Grooving [Specified in 12" increments, from left to right. 24" maximum, from either side.] Special grooved surface cleaning tool provided
- USPH approved Griddle Stand, with adjustable flanged mounting feet
- Overhead Control Box [-R Model] for remote bulkhead mounting



All models
[Front View/Elevation]
Width varies with model



All Models
[Right Side View]



All Models
[Top View/Plan]
LGC-60, LGC-72 require 2 **E** connections

| Model | Height x Width x Depth (Including standard legs) | Clearance from combustible surface | Weight | | Freight Class |
|-------|---|---------------------------------------|--------------------|--------------------|------------------|
| | | | Actual | Shipping | |
| CLG24 | 19.0" x 24.0" x 30.2" 483mm x 610mm x 767mm | Sides: 2" Back: 2" | 330 lbs. 150 kg | 380 lbs. 173 kg | 85 |
| CLG36 | 19.0" x 36.0" x 30.2" 483mm x 914mm x 767mm | | 360 lbs. 164 kg | 410 lbs. 186 kg | 85 |
| CLG48 | 19.0" x 48.0" x 30.2" x 1219mm x 767mm | | 475 lbs. 216 kg | 525 lbs. 239 kg | 85 |
| CLG60 | 19.0" x 60" x 30.2" 483mm x 1524mm x 767mm | | 615 lbs. 280 kg | 665 lbs. 302 kg | 85 |
| CLG72 | 19.0" x 72.0" x 30.2" x 1830mm x 767mm | | 750 lbs. 341 kg | 800 lbs. 364 kg | 85 |

| Model | E Electrical Requirements | | | |
|-------|----------------------------------|---------------|-----------|-----------|
| | Voltage | Total kW | Phase | Amps/Line |
| CLG24 | 440 - 50/60 | 12.0 | 23.6 | N/A |
| CLG36 | 440 - 50/60 | 18.0 | 23.6 | N/A |
| CLG48 | 440 - 50/60 | 24.0 | 36.8 | N/A |
| CLG60 | 440 - 50/60 | 30.0 [12/18]* | 23.6/23.6 | N/A |
| CLG72 | 440 - 50/60 | 36.0 [18/18]* | 23.6/23.6 | N/A |

Due to continuous improvements, specifications subject to change without notice.



Sheet No. LCLS-1 (rev. 06/17)

LANG MANUFACTURING • 10 SUNNEN DR. ST. LOUIS, MO 63143
PHONE: 314-678-6315 • FAX: 314-781-3636 • www.langworld.com