



# POWER PACK - WATER COOLED

PREMIUM - 1 PUMP - 3,600 BTUs

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Anti-vibration pads reduce motor noise.
- Exterior sight glass to verify glycol bath level.
- Rugged stainless steel cabinet.




Reverse side showing water connections.



## MMPP4302-WC

Water Cooled:  
Designed for spaces with limited air circulation or high ambient temperature.



5 - 20P



| Part No.                             | Description                               | Shipping Weight  |
|--------------------------------------|---|------------------|
| <input type="checkbox"/> MMPP4302-WC | Water cooled power pack, 1 pump and motor | 80 kg<br>175 lbs |

**Operating Performance**

|  |                               |   |   |
|--|-------------------------------|---|---|
| <b>Compressor</b>                        | 1/2 HP                        | <b>Pump Type</b>                        | Rotary Vane   |
| <b>BTU per hour</b>                      | 3,600                         | <b>Push In Connector</b>                | 12.7mm (1/2") O.D.  |
| <b>Plug Type (NEMA #)</b>                | 5-20P                         | <b>Water Inlet &amp; Outlet Fitting</b> | Female 3/8" NPT   |
| <b>Voltage</b>                           | 115                           | <b>Minimum Water Pipe Size</b>          | 3/8"  |
| <b>Running</b>                           | 14.9A                         | <b>Inlet Water Pressure</b>             | Minimum 40 psi / Maximum 120 psi  |
| <b>Refrigerant</b>                       | R-134a                        | <b>Water Usage</b>                      | .3 GPM. Water is only used when the temperature of the condenser rises high enough to open the cooling inlet valve. This is approximately 40% of the operating time depending on ambient temperature and usage. |
| <b>Charge</b>                            | 0.51 kg (18 oz)               |   |   |
| <b>Refrigerant Running Pressure</b>      | 18 (low) 140 (high)           |   |   |
| <b>Bath Capacity</b>                     | 43.5 litre (11.5 gallons)     |   |   |
| <b>Condenser Inlet Water Temperature</b> | Minimum 45° F / Maximum 80° F |   |   |

**Dimensions**

