

Refrigeration Equipment 2-Door Work Top Freezer 48 " Long

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



738304 (KCHUCWT48F)

2-Door Work Top Freezer 48
" Long

Short Form Specification

Item No. _____

2-door freezer counter top, with worktop, with exterior back panel, exterior bottom panel, and exterior top panel in galvanized steel, exterior side panel in 430 stainless steel; interior back, top and bottom panels in 304 stainless steel. Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and temperature control. Vinyl heavy duty adjustable, easy to handle and clean shelves. External temperature display.

R290 gas in refrigeration circuit.
ETL Safety and Sanitation certified.
3/5 Years warranty.

Main Features

- External temperature display.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Heavy duty Vinyl coated steel shelves.
- Cabinet completely insulated with high density polyurethane for low environmental impact.

Construction

- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.


Sustainability

- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.

Optional Accessories

- 1 ADJUSTABLE FOOT PNC 206445

APPROVAL: _____



Electric

Supply voltage:

738304 (KCHUCWT48F) 115 V/1 ph/60 Hz

Electrical power, max:

0.41 kW

Plug type:

USA NEMA 5-15P

Capacity:

Gross capacity: 12 cu.feet

Key Information:

Door hinges:

1 Left+1 Right

Capacity:

12 cu.ft.

External dimensions, Width:

48 1/4" (1225 mm)

External dimensions, Depth:

29 15/16" (760 mm)

External dimensions, Height:

39 5/8" (1007 mm)

Number and type of doors:

2 Full

Internal Dimensions (depth):

22 13/16" / (580 mm)

Internal Dimensions (height):

23 1/2" / (597 mm)

Internal Dimensions (width):

42 1/2" / (1080 mm)

Shipping height:

42 1/8" (1070 mm)

Shipping weight:

276 lbs (125 kg)

Shipping volume:

38.24 ft³ (1.08 m³)

Number and type of grids (included):

2 - Vinyl-Coated Steel

Type of external material:

Stainless Steel

Type of internal material:

Polystyrene

Warranty:

3 / 5 years

Approvals

ETL C&US;ETL SANITATION

Refrigeration Data

Compressor power:

1/3 hp

Operating temperature min.:

-9.4 °F

Operating temperature max.:

8.6 °F

Condenser type:

Fin & tube

Defrost type:

Auto Defrost

Sustainability

Current consumption:

4 Amps

Refrigerant type:

R290

Refrigerant weight:

100 g