

# Hamilton Beach®

COMMERCIAL

# BigRig™

## Family of Immersion Blenders



Incredibly  
**FAST**  
Results

Blend, chop,  
mix, puree,  
and emulsify

Most powerful motor in its class\*

Comfortable 2-position handle and ergonomic shaft grip

Variable speed ThumbDrive™ with color-coded light for immediate feedback

100% sealed, removable stainless steel shaft

Continuous run operation for high-volume blending

Serviceable 12 ft./365cm power cord designed for high visibility

Assurance with 2 year replacement warranty

\* 800 watts for 120V; 1000 watts for 220-240V

### Various Sizes Available



### Interchangeable Shaft

12"/305mm, 14"/355mm, 16"/406mm,  
18"/457mm, and 21"/533mm  
(sold separately)

For more Good Thinking® visit [hamiltonbeachcommercial.com](http://hamiltonbeachcommercial.com)

NSF®



**Stainless Steel Shaft with Ergonomic Grip**  
Detaches to let you change to a different-size shaft



**ThumbDrive™ Variable Speed Dial**  
With color-coded light for immediate feedback about blender status

**Blend Volume Chart**  
12"/305mm shaft - up to 6 gal. (23 L)  
14"/355mm shaft - up to 14 gal. (53 L)  
16"/406mm shaft - up to 23 gal. (87 L)  
18"/457mm shaft - up to 32 gal. (121 L)  
21"/533mm shaft - up to 42 gal. (158 L)

**Patent-Pending Serviceable Cord**  
Helps extend the blender's life



**Stainless Steel Blade with Guard**  
Blends, chops, purees, or emulsifies ingredients quickly



**Ergonomic Design with Light-Touch Controls**  
Offers multiple hand positions for comfort



**Optional 10"/25cm Whisk**  
Lets you whip and aerate ingredients (sold separately)



**Wall Mount and Cord Holder**  
For neat, easy storage

## IMMERSION BLENDER SERIES

**SPECIFICATIONS:**

Model	Shaft Length	Shipping Weight (lbs)	Shipping Weight (kg)
HMI012	30.5" (78 cm)	13.5	6.1
HMI014	32.5" (82 cm)	13.7	6.2
HMI016	34.5" (88 cm)	13.9	6.3
HMI018	36.5" (93 cm)	14.1	6.4
HMI021	39.5" (100 cm)	15.2	7.0
HMI02W	Whisk only 19.5" (49 cm) 4.5" (11 cm)	6.0	2.7

Standard: unit comes with power base, stainless steel shaft, and wall-mount hanger  
Controls: Variable speed dial, trigger, power button  
Warranty: 2 year parts & labor  
Blend speeds: min. 3,000 rpm - max. 15,000 rpm

HMI (120V)	HMI-CE/-UK (230V)
120V~, 60 Hz, 800 W	220-240V~, 50-60 Hz, 1000 W, IPX1