Skyfood
Equipment LLC

Easy Weigh

LS-100
PRICE COMPUTING AND PRINTABLE SCALE

- Rugged design for years of maintenance-free operation
- Heavy gauge Large Stainless Steel platter
- Quick-Response Weight display
- Standard 1000 PLU memory with Battery-Backup with 672 Characters per PLU!
- Tough high quality UV-sealed keypad
- Alphanumeric LCD display for easy programming with Backlight
- Extensive Label Format Library
- Menu-driven simple scale programming
- Quick operation keypad for high throughput
- Standard RS-232 serial port
- Networking available on some model
- Can Print Ingredients & Safe Handling labels
- Bright red LED Displays for Weight & Pricing
- 60 Large Direct PLU Keys with Removable Template!
- Cassette Loaded High Speed Thermal Printer
- Advanced Windows Scale Software!

The LS-100 comes with a universal power supply and a removable power cord. Changing the PC-style power cord & using kilogram calibration, you can freely adapt to any foreign electrical outlets. Additionally, the LS-100 has an RS-232 serial port for connection to a PC or another LS-100. Using the serial port, our Scale-Copy feature allows you to clone a scale in approximately 30 seconds!

ORDER TOLL FREE 800-445-6601
www.skyfood.us

LS-100
PRICE COMPUTING AND PRINTABLE SCALE

Easy Weigh

High Speed Printing & Weighing

Using a state-of-the-art high speed 100mm/sec (4" sec) durable thermal print head, the LS-100 was built with the most demanding "prepack" applications in mind. With our innovative cassette drawer mechanism, the LS-100 can be loaded with labels quickly & easily. With a larger label roll capacity than most printing scales, the LS-100 allows for the most productivity with minimal down-time. We combined all these great features with an extensive Label Format Library containing the most popular label formats as well as many of our own custom label styles. With this much flexibility, the LS-100 can be easily adapted to replace any scale without having to change your current label stock! And with display & printer support for many languages (English, Korean, Spanish...) combined with support for ingredients, safe handling, By-weight, By-count, or even simple label printing, you can never go wrong with the LS-100!

LS-100

Shipping Weight	32 lb
Maximum Capacity	0 to 30 lb x 0.01 lb / 30 to 60 lb x 0.02 lb (Dual Range / Multi-interval)
Maximum Tare	Half Capacity, 0.00 to 29.99 lb
Printer Specifications	100 mm/sec (4"/sec) Direct Thermal Printer 60 mm (2.4") wide printing element
Label Roll Specifications	120 mm (4.7 ") Max diameter (outer) for label rolls, 15 mm (0.6 ") min diameter (inner core)
Label Dimensions	30 ~ 60 mm (1.2 ~ 2.4") Max width, 100 mm (4") Max length
Direct PLU Keys	60 Speed Keys, includes a blank template, can print templates using a PC & Printer
Memory Specifications	1000 PLUs (max with 512 KB NiCd battery-backed SRAM)
LCD Display with Backlight	256 x 32 pixel, monochrome graphical Liquid Crystal Display
Red LED 8-Segment Displays	Weight: 5 Digits, 999.99 (60 lb max) Unit Price: 6 Digits, 9999.99 (7 digits max) Total Price: 7 Digits, 9999.99 (8 digits max)
Communications	115,200 bps serial port (COM1), for PC-to-Scale or Scale-to-Scale. (Not for Networking)
Platter Size	Width: 415 mm / 16.3 " - Length: 260 mm / 10.2 " - Stainless Steel
Product Dimensions	Width: 460 mm / 18.1 " - Length: 460 mm / 18.1 " - Height: 490 mm / 19.3 "
Legal For Trade (NTEP)	CC Number 02-061, Temperature: -10ºC to 40ºC (14 ºF to 104 ºF), Class III
Power Requirements	85 Volts to 240 Volts AC @ 50/60 Hz $\pm$ 5%, 100 Watts (Printing) to 40 Watts (Standby) 1.6Amp, 250Volt, 20mm fuse