

Aurora Reach-In Freezer, Solid Door, Stainless Steel

ITEM: 59023 59025
 MODEL: FR-CN-0737E-HC FR-CN-1372E-HC



29" wide
59023




54" wide
59025

Aurora stainless steel reach-in freezer – your ideal kitchen partner for storing frozen food and ingredients.


Spacious reach-in freezer crafted with enduring quality. Sleek design using stainless steel material featuring high-efficiency components. This freezer is perfect for your restaurant, cafe, or bakery for storing pre-prepped ingredients and portions of your signature dishes, fries or proteins.

FEATURES:

- **Incredibly Spacious – Adjustable Shelves**
This unit is extremely spacious with a large cabinet with multiple adjustable shelves, thus maximizing your commercial kitchen space.
- **Powerful, environmentally safe refrigeration system**
Uses with R290 refrigerant to keep your ingredients and fully-prepared foods at safe frozen temperatures. The compressor is bottom mounted for energy efficiency, and also raises the bottom shelf, so all your frozen ingredients are within reach and you don't have to bend as much during loading and unloading.
- **Digital Temperature Control**
Easily adjust the freezer cabinet's temperature with the digital temperature controller. The clear LCD readout also helps keep track of the unit's temperature.
- **Autodefrost System**
This unit has an automatic defrost feature which eliminates the need to spend invaluable time cleaning out the ice.



WARRANTY
 2 YEARS PARTS AND LABOUR
 5 YEARS ON COMPRESSOR






TECHNICAL SPECIFICATION




Features	29" wide with 20.6 cu.ft. capacity	54" wide with 41.3 cu.ft. capacity
Item	59023	59025
Model	FR-CN-0737E-HC	FR-CN-1372E-HC
Capacity	20.6 cu. ft. (583 L)	41.3 cu.ft. (1169 L)
Number of Doors	1 Swing Door - Solid Door	2 Swing Doors - Solid Door
Self-Closing Door	Yes	
Number of Shelves	3	6
Shelf Capacity (kg/pc)	88.2 lb. (40 kg.)	
Shelf Material	Plastic Coated	
Number of Casters	Yes (4)	
Power	456 W	780 W
Amps	4.9A	8.5A
Electrical	110-120V / 60Hz / 1Ph	
Temperature Controller	Digital	
Temperature Range	-22.2 to -17.8°C (-8 to 0°F)	
Refrigerant	R290	
Insulation Material	Cyclopentane	
Cooling System	Ventilated	
Defrosting	Automatic	
Interior Dimensions (WDH)	24.4" x 27.1" x 53.5" (620 x 688 x 1360 mm)	49.4" x 27.1" x 53.5" (1255 x 688 x 1360 mm)
Net Weight	282.2 lb. (128 kg.)	447.5 lb. (203 kg.)
Net Dimensions (WDH)	29" x 32.2" x 82.5" (736 x 818 x 2095 mm)	54" x 32.2" x 82.5" (1371 x 818 x 2095 mm)
Gross Weight	322 lb. (146 kg.)	531.3 lb. (241 kg.)
Gross Dimensions (WDH)	30.3" x 34.1" x 84.4" (770 x 865 x 2145 mm)	56.5" x 34.6" x 85" (1435 x 880 x 2160 mm)
Plug Type	NEMA 5-20P	

** This equipment is intended for indoor environment using where ambient temperature do not exceed 24°C(75°F) & 55% relative humidity*

TECHNICAL DRAWING (measurements are in mm)



29" wide
59023



54" wide
59025